

INTRIGUE LT ADVANCED 2



SPECS

FRAME	
SIZES	XS, S: MX only, M, L: 29" F&R out of the box, MX compatible
COLORS	Mushroom
FRAME	Advanced-grade composite front and rear triangles, 150mm Maestro Suspension, flip chip – Maestro 3, integrated down tube storage
FORK	Marzocchi Bomber Z1, 160mm, Rail damper, Boost 15x110 Kabolt, tapered, 44mm offset
SHOCK	Fox Float Performance 185x55, custom tuned for Liv
COMPONENTS	
HANDLEBAR	Giant Contact TR35, alloy, 35mm, 20mm rise XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPS	Liv Tactal Pro Single Lock-On XS/S: 120mm, M/L: 130mm
STEM	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
SEATPOST	TranzX travel-adjustable dropper, remote XS: 125mm travel/ 30.9 x 390mm S: 120-150mm travel / 30.9 x 390mm M: 150mm travel / 30.9 x 440mm L: 150mm travel / 30.9 x 440mm
SADDLE	Liv Sylvia
PEDALS	platform
DRIVETRAIN	
SHIFTERS	Shimano Deore, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano Deore, Shadow +
BRAKES	Shimano BR-MT420, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
BRAKE LEVERS	Shimano BL-MT401
CASSETTE	Shimano Deore M6100, 10x51
CHAIN	KMC X12
CRANKSET	Praxis Cadet, steel chain ring 30t, 52mm chainline S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	Praxis, press fit

WHEELS	
RIMS	Giant TRX 2 Carbon WheelSystem, 30mm inner width XS/S: [F] 29, [R] 27.5 M/L: [F] 29, [R] 29
HUBS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
SPOKES	Sapim
TIRES	Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	MRP 1259-HD2CS-0001 chain guide, 3M tailgate protector, tubeless prepared, integrated down tube storage bag, max tire size 2.5", max chainring size 32t

GEOMETRY

FRAME	XS			S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	370			390			420			450		
Seat Post Insertion Depth (mm)	230			250			280			310		
Seat Tube Angle	76,2° 76,6° 77,0°			76,2° 76,6° 77,0°			77,3° 77,6° 78,0°			77,3° 77,6° 78,0°		
Top Tube Length (mm)	552 552 550			567 566 565			581 580 579			603 602 601		
Head Tube Length (mm)	95			95			100			110		
Head Tube Angle	64,7° 65,1° 65,5°			64,6° 65,1° 65,5°			64,8° 65,1° 65,5°			64,8° 65,1° 65,5°		
Fork Rake (mm)	44			44			44			44		
Trail (mm)	131 127,9 124,8			131,6 127,8 124,8			130,6 127,7 124,8			130,5 127,7 124,8		
Wheelbase (mm)	1166 1166 1164			1183 1180 1179			1208 1207 1207			1232 1231 1231		
Chain Stay Length (mm)	443 442 440			443 442 440			443 442 440			443 442 440		
Bottom Bracket Drop (mm)	25 20 15			24 20 15			35 30 25			35 30 25		
Stack (mm)	629 627 624			628 627 624			628 625 622			637 634 633		
Reach (mm)	398 402 406			413 417 421			439 442 447			459 462 466		
Stand Over Height (mm)	613 613 613			674 674 674			712 712 712			750 750 750		
Handlebar Width (mm)	760			760			760			780		
Stem Length (mm)	40			50			50			50		
Crank Length (mm)	165			170			170			170		
Wheel Size	F 29 R 27.5			F 29 R 27.5			29"			29"		

All specifications listed are subject to change without notice.