



INTRIGUE LT ADVANCED



SPECS

FRAME	
SIZES	XS, S: MX only, M, L: 29" F&R out of the box, MX compatible
COLOURS	Raw Carbon/Chrome
FRAME	Advanced-grade composite front and rear triangles, 150mm Maestro Suspension, flip chip - Maestro 3, 12x148mm thru-axle, integrated down tube storage
FORK	Fox 38 Performance Elite, 170mm, GRIP 2 damper, Boost 15x110 Kabolt, tapered, 44mm offset
SHOCK	Fox Float X Performance Elite 185x55, 2 position adjust, custom tuned for Liv, recommended sag 30%
COMPONENTS	
HANDLEBAR	Giant Contact SLR TR35, composite, 20mm rise, 35mm XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPS	Liv Tactal Pro Single Lock-On XS/S: 120mm, M/L: 130mm
STEM	Giant Contact SL 35 XS: 40mm, S: 50mm, M: 50mm, L: 50mm
SEATPOST	Giant Contact Switch AT dropper, remote XS: 140-170mm travel/ 30.9x470mmS: 140-170mm travel/ 30.9x470mmM: 170-200mm travel/30.9x530mmL: 170-200mm travel/30.9x530mm
SADDLE	Liv Sylvia
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, discrete clamp, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM GX T-Type
BRAKES	TRP EVO DH-R, hydraulic, RT-66 rotors[F]203mm, [R]180mm
BRAKE LEVERS	TRP HD-R EVO
CASSETTE	SRAM GX T-Type, 10x52
CHAIN	SRAM GX T-Type
CRANKSET	SRAM GX Eagle Transmission, DUB, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
HUBS	[F] Giant MTB alloy, six-bolt, [R] Giant MTB alloy, 72 POE (Points of Engagement), six-bolt, XD driver body
SPOKES	Sapim, 28, straight pull, DBL Technology
TIRES	Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	MRP AMG CS chain guide, 3M tailgate protector, tubeless prepared, integrated down tube storage bag, max tire size 2.5", max chaining size 32t

Suggested Retail Price (CDN): \$7,999.00

FRAME GEOMETRY

FRAME	XS			S			M		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	370			390			420		
Seat Post Insertion Depth (mm)	230			250			280		
Seat Tube Angle	76.2°	76.6°	77.0°	76.2°	76.6°	77.0°	77.3°	77.6°	78.0°
Top Tube Length (mm)	552	552	550	567	566	565	581	580	579
Head Tube Length (mm)	95			95			100		
Head Tube Angle	64.7°	65.1°	65.5°	64.6°	65.1°	65.5°	64.8°	65.1°	65.5°
Fork Rake (mm)	44			44			44		
Trail (mm)	131	127.9	124.8	131.6	127.8	124.8	130.6	127.7	124.8
Wheelbase (mm)	1166	1166	1164	1183	1180	1179	1208	1207	1207
Chain Stay Length (mm)	443	442	440	443	442	440	443	442	440
Bottom Bracket Drop (mm)	25	20	15	24	20	15	35	30	25
Stack (mm)	629	627	624	628	627	624	628	625	622
Reach (mm)	398	402	406	413	417	421	439	442	447
Stand Over Height (mm)	613	613	613	674	674	674	712	712	712
Handlebar Width (mm)	760			760			760		
Stem Length (mm)	40			50			50		
Crank Length (mm)	165			170			170		
Wheel Size	F 29	R 27.5		F 29	R 27.5		29"		

All prices and specifications are subject to change without notice.