

INTRIGUE LT ADVANCED PRO 0



СПЕЦИФИКАЦИИ

РАМКА	
РАЗМЕР	XS, S: MX only, M, L: 29" F&R out of the box, MX compatible
ЦВЯТ	Mirage
РАМКА	Advanced-Grade Composite front and rear triangles, 150mm Maestro Suspension, flip chip – Maestro 3, integrated down tube storage
ВИЛКА	Fox 36 Factory Live Valve, 160mm, FIT4 damper, Boost, 15x110, Kabolt, tapered, 44mm offset
ЗАДЕН АМОРТИСЬОР	Fox Factory Live 185x55, custom tuned for Liv
КОМПОНЕНТИ	
КОРМИЛО	Giant Contact SLR TR35, composite, 35mm, 20mm rise XS: 760mm, S: 760mm, M: 760mm, L: 780mm
ГРИПОВЕ	Liv Tactal Pro Single Lock-On XS and S: 110mm, M and L: 120mm
ЛАПА	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
КОЛЧЕ ЗА СЕДАЛКА	TranzX travel-adjustable dropper, remote XS: 120-150mm travel / 30.9 x 459mm S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 140-170mm travel / 30.9 x 499mm
СЕДАЛКА	Liv Sylvia
ПЕДАЛИ	platform
DRIVETRAIN	
КОМАНДИ	SRAM AXS Rocker, 1x12
ПРЕДЕН ДЕРАЙЛЪОР	N/A
ЗАДЕН ДЕРАЙЛЪОР	SRAM XX1 Eagle AXS
СПИРАЧКИ	Shimano XTR M9120, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
РЪКОХВАТКИ ЗА СПИРАЧКИ	Shimano XTR, BL-M9100
КАСЕТА	SRAM XX1 Eagle AXS, 10x52
ВЕРИГА	SRAM X01 Eagle
КУРБЕЛ	SRAM XX1 Eagle DUB, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
СРЕДНА КАСЕТА	SRAM DUB, press fit

КАПЛИ	
ШИНИ	Zipp 3ZERO MOTO XS and S: [F] 29", [R] 27.5" M and L: [F] 29", [R] 29"
ГЛАВИНИ	Zipp 3ZERO MOTO
СПИЦИ	Zipp 3ZERO MOTO
ГУМИ	[Size XS, S, M and L, F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [Size XS and S, R] Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless [Size M and L, R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
ЕКСТРИ	MRP AMg V2 chainguide, 3M tailgate protector, tubeless prepared, max tire size 2.5", max chainring size 32t, integrated down tube storage bag

ГЕОМЕТРИЯ

РАМКА	XS			S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	370			390			420			450		
Seat Tube Angle	76,2°	76,6°	77,0°	76,2°	76,6°	77,0°	77,3°	77,6°	78,0°	77,3°	77,6°	78,0°
Top Tube Length (mm)	552	552	550	567	566	565	581	580	579	603	602	601
Head Tube Length (mm)	95			95			100			110		
Head Tube Angle	64,7°	65,1°	65,5°	64,6°	65,1°	65,5°	64,8°	65,1°	65,5°	64,8°	65,1°	65,5°
Fork Rake (mm)	44			44			44			44		
Trail (mm)	131	127,9	124,8	131,6	127,8	124,8	130,6	127,7	124,8	130,5	127,7	124,8
Wheelbase (mm)	1166	1166	1164	1183	1180	1179	1208	1207	1207	1232	1231	1230
Chain Stay Length (mm)	443	442	440	443	442	440	443	442	440	443	442	440
Bottom Bracket Drop (mm)	25	20	15	24	20	15	35	30	25	35	30	25
Stack (mm)	629	627	624	628	627	624	628	625	622	637	634	631
Обсер (mm)	398	402	406	413	417	421	439	442	447	459	462	467
Stand Over Height (mm)	727	727	727	750	750	750	760	760	760	770	770	770
Ширина на Кормило (mm)				760			760			780		
Дължина на Лапа (mm)	40			50			50			50		
Дължина на Курбел (mm)	165			170			170			170		
Размер на Каплите	F29"/R27.5			F29"/R27.5			29"			29"		

All specifications listed are subject to change without notice.