INTRIGUE LT ADVANCED PRO 0



SPECIFIKACE

RÁM	
VELIKOSTI	XS, S: MX only, M, L: 29" F&R out of the box, MX compatible
BARVA	Mirage
RÁM	Advanced-Grade Composite front and rear triangles, 150mm Maestro Suspension, flip chip – Maestro 3, integrated down tube storage
VIDLICE	Fox 36 Factory Live Valve, 160mm, FIT4 damper, Boost, 15x110, Kabolt, tapered, 44mm offset
TLUMIČ	Fox Factory Live 185x55, custom tuned for Liv
KOMPONENTY	
ŘÍDÍTKA	Giant Contact SLR TR35, composite, 35mm, 20mm rise XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPY	Liv Tactal Pro Single Lock-On XS and S: 110mm, M and L: 120mm
PŘEDSTAVEC	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
SEDLOVKA	TranzX travel-adjustable dropper, remote XS: 120-150mm travel / 30.9 x 459mm S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 140-170mm travel / 30.9 x 499mm
SEDLO	Liv Sylvia
PEDÁLY	platform
OSAZENÍ	
ŘAZENÍ	SRAM AXS Rocker, 1x12
PŘESMYKAČ	N/A
PŘEHAZOVAČKA	SRAM XX1 Eagle AXS
BRZDY	Shimano XTR M9120, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
BRZDOVÉ PÁKY	Shimano XTR, BL-M9100
KAZETA	SRAM XX1 Eagle AXS, 10x52
ŘETĚZ	SRAM X01 Eagle
KLIKY	SRAM XX1 Eagle DUB, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
STŘED	SRAM DUB, press fit

KOLA	
RÁFKY	Zipp 3ZERO MOTO XS and S: [F] 29"", [R] 27.5"" M and L: [F] 29"", [R] 29"
NÁBOJE	Zipp 3ZERO MOTO
DRÁTY	Zipp 3ZERO MOTO
PLÁŠTĚ	[Size XS, S, M and L, F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [Size XS and S, R] Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless [Size M and L, R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
DOPLŇKY	MRP AMg V2 chainguide, 3M tailgate protector, tubeless prepared, max tire size 2.5", max chainring size 32t, integrated down tube storage bag

GEOMETRIE

RÁM	XS	S	M	L
	LOW | MID | HIGH	LOW | MID | HIGH	LOW | MID | HIGH	LOW | MID | HIGH
Délka sedlové trubky (mm)	370	390	420	450
Úhel sedlové trubky	76,2° | 76,6° | 77,0°	76,2° | 76,6° | 77,0°	77,3° | 77,6° | 78,0°	77,3° | 77,6° | 78,
Délka horní trubky (mm)	552 | 552 | 550	567 | 566 | 565	581 | 580 | 579	603 | 602 | 601
Délka hlavové trubky (mm)	95	95	100	110
Úhel hlavové trubky	64,7° | 65,1° | 65,5°	64,6° | 65,1° | 65,5°	64,8° | 65,1° | 65,5°	64,8° | 65,1° | 65,
Offset vidlice (mm)	44	44	44	44
Trail (mm)	131 | 127,9 | 124,8	131,6 | 127,8 | 124,8	130,6 | 127,7 | 124,8	130,5 | 127,7 | 12
Rozvor (mm)	1166 | 1166 | 1164	1183 | 1180 | 1179	1208 | 1207 | 1207	1232 | 1231 | 123
Délka řetězové vzpěry (mm)	443 | 442 | 440	443 | 442 | 440	443 | 442 | 440	443 | 442 | 440
Bottom Bracket Drop (mm)	25 | 20 | 15	24 | 20 | 15	35 | 30 | 25	35 | 30 | 25
Stack (mm)	629 | 627 | 624	628 | 627 | 624	628 | 625 | 622	637 | 634 | 631
Reach (mm)	398 | 402 | 406	413 | 417 | 421	439 | 442 | 447	459 | 462 | 467
Výška rámu od země (mm)	727 | 727 | 727	750 | 750 | 750	760 | 760 | 760	770 | 770 | 770
Šířka řídítek (mm)	760	760	760	780
Délka představce (mm)	40	50	50	50
Délka klik (mm)	165	170	170	170
Rozměr kol	F29"/R27.5	F29"/R27.5	29"	29"

Děláme vše pro to, aby veškeré údaje na tomto webu byly správné a aktuální. Přesto si ale musíme vyhradit právo na případné změny specifikací, barevného provedení a cen, a to bez předchozího upozornění. Děkujeme za pochopení.