INTRIGUE LT ADVANCED PRO 0



SPECS

ΣΚΕΛΕΤΌΣ	
ΜΕΓΈΘΗ	XS, S: MX only, M, L: 29" F&R out of the box, MX compatible
ΧΡΏΜΑΤΑ	Mirage
ΣΚΕΛΕΤΌΣ	Advanced-Grade Composite front and rear triangles, 150mm Maestro Suspension, flip chip – Maestro 3, integrated down tube storage
ΠΙΡΟΎΝΙ	Fox 36 Factory Live Valve, 160mm, FIT4 damper, Boost, 15x110, Kabolt, tapered, 44mm offset
ΑΝΆΡΤΗΣΗ	Fox Factory Live 185x55, custom tuned for Liv
ΕΞΑΡΤΉΜΑΤΑ	
ΤΙΜΌΝΙ	Giant Contact SLR TR35, composite, 35mm, 20mm rise XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPS	Liv Tactal Pro Single Lock-On XS and S: 110mm, M and L: 120mm
ΛΑΙΜΌΣ ΤΙΜΟΝΙΟΎ	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
ΛΑΙΜΌΣ ΣΈΛΛΑΣ	TranzX travel-adjustable dropper, remote XS: 120-150mm travel / 30.9 x 459mm S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 140-170mm travel / 30.9 x 499mm
ΣΈΛΛΑ	Liv Sylvia
ΠΕΝΤΆΛ	platform
ΜΕΤΆΔΟΣΗ	
ΛΕΒΙΈ ΤΑΧΥΤΉΤΩΝ	SRAM AXS Rocker, 1x12
ΝΤΕΡΑΓΙΈΡ ΕΜΠΡΌΣΘΙΟ	N/A
ΝΤΕΡΑΓΙΈΡ ΟΠΊΣΘΙΟ.	SRAM XX1 Eagle AXS
ΦΡΈΝΑ	Shimano XTR M9120, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
ΜΑΝΈΤΤΕΣ ΦΡΈΝΩΝ	Shimano XTR, BL-M9100
CASETTE Ή ΕΛΕΎΘΕΡΟ	SRAM XX1 Eagle AXS, 10x52
ΑΛΥΣΊΔΑ	SRAM X01 Eagle
ΔΙΣΚΟΒΡΑΧΊΩΝΑΣ	SRAM XX1 Eagle DUB, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
ΣΤΕΦΆΝΙΑ	Zipp 3ZERO MOTO XS and S: [F] 29"", [R] 27.5"" M and L: [F] 29"", [R] 29"
ΚΈΝΤΡΑ	Zipp 3ZERO MOTO
ΑΚΤΊΝΕΣ	Zipp 3ZERO MOTO
ΕΛΑΣΤΙΚΆ	[Size XS, S, M and L, F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [Size XS and S, R] Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless [Size M and L, R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	MRP AMg V2 chainguide, 3M tailgate protector, tubeless prepared, max tire size 2.5", max chainring size 32t, integrated down tube storage bag

ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΌΣ	XS	S	M	L
	LOW | MID | HIGH	LOW | MID | HIGH	LOW | MID | HIGH	LOW | MID | HIGH
Seat Tube Length (mm)	370	390	420	450
Seat Tube Angle	76,2° | 76,6° | 77,0°	76,2° | 76,6° | 77,0°	77,3° | 77,6° | 78,0°	77,3° | 77,6° | 78,0
Top Tube Length (mm)	552 | 552 | 550	567 | 566 | 565	581 | 580 | 579	603 | 602 | 601
Head Tube Length (mm)	95	95	100	110
Head Tube Angle	64,7° | 65,1° | 65,5°	64,6° | 65,1° | 65,5°	64,8° | 65,1° | 65,5°	64,8° | 65,1° | 65,5
Fork Rake (mm)	44	44	44	44
Trail (mm)	131 | 127,9 | 124,8	131,6 | 127,8 | 124,8	130,6 | 127,7 | 124,8	130,5 | 127,7 | 124
Wheelbase (mm)	1166 | 1166 | 1164	1183 | 1180 | 1179	1208 | 1207 | 1207	1232 | 1231 | 1231
Chain Stay Length (mm)	443 | 442 | 440	443 | 442 | 440	443 | 442 | 440	443 | 442 | 440
Bottom Bracket Drop (mm)	25 | 20 | 15	24 | 20 | 15	35 | 30 | 25	35 | 30 | 25
Stack (mm)	629 | 627 | 624	628 | 627 | 624	628 | 625 | 622	637 | 634 | 631
Reach (mm)	398 | 402 | 406	413 | 417 | 421	439 | 442 | 447	459 | 462 | 467
Stand Over Height (mm)	727 | 727 | 727	750 | 750 | 750	760 | 760 | 760	770 | 770 | 770
Handlebar Width (mm)	760	760	760	780
Stem Length (mm)	40	50	50	50
Crank Length (mm)	165	170	170	170
Wheel Size	F29"/R27.5	F29"/R27.5	29"	29"

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση