

# INTRIGUE LT ADVANCED PRO 0



## SPECS

| FRAME                   |  |
|-------------------------|--|
| <b>SIZES</b>            | XS, S: MX only, M, L: 29" F&R out of the box, MX compatible  |
| <b>COLOURS</b>          | Mirage   |
| <b>FRAME</b>            | Advanced-Grade Composite front and rear triangles, 150mm Maestro Suspension, flip chip - Maestro 3, integrated down tube storage |
| <b>FORK</b>             | Fox 36 Factory Live Valve, 160mm, FIT4 damper, Boost, 15x110, Kabolt, tapered, 44mm offset                                       |
| <b>SHOCK</b>            | Fox Factory Live, custom tuned for Liv   |
| COMPONENTS              |  |
| <b>HANDLEBAR</b>        | Giant Contact SLR TR35, composite  |
| <b>GRIPS</b>            | Liv Tactal single lock-on  |
| <b>STEM</b>             | Giant Contact SL   |
| <b>SEATPOST</b>         | TranzX travel-adjustable dropper, remote   |
| <b>SADDLE</b>           | Liv Sylvia   |
| <b>PEDALS</b>           | N/A  |
| DRIVETRAIN              |  |
| <b>SHIFTERS</b>         | SRAM AXS Rocker, 1x12  |
| <b>FRONT DERAILLEUR</b> | N/A  |
| <b>REAR DERAILLEUR</b>  | SRAM XX1 Eagle AXS   |
| <b>BRAKES</b>           | Shimano XTR M9120, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm  |
| <b>BRAKE LEVERS</b>     | Shimano XTR, BL-M9100  |
| <b>CASSETTE</b>         | SRAM XX1 Eagle AXS, 10x52  |
| <b>CHAIN</b>            | SRAM X01 Eagle   |
| <b>CRANKSET</b>         | SRAM XX1 Eagle DUB, 30t, 55mm chainline  |
| <b>BOTTOM BRACKET</b>   | SRAM DUB, press fit  |

| WHEELS        |   |
|---------------|---|
| <b>RIMS</b>   | Zipp 3ZERO MOTO XS/S: [F] 29", [R] 27.5 M/L: [F]29", [R]29" (*Quarq TyreWiz not included)   |
| <b>HUBS</b>   | Zipp 3ZERO MOTO ZM2   |
| <b>SPOKES</b> | Zipp 3ZERO MOTO   |
| <b>TYRES</b>  | [Size XS, S, M and L, F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [Size XS and S, R] Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless [Size M and L, R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless |
| <b>EXTRAS</b> | MRP AMg V2 chainguide, 3M tailgate protector, tubeless prepared, max tyre size 2.5", max chainring size 32t   |

**Price: \$14,999.00**

## GEOMETRY

| FRAME                    | XS                    |       |       | S                     |       |       | M                     |       |       | L                     |       |       |
|--------------------------|-----------------------|-------|-------|-----------------------|-------|-------|-----------------------|-------|-------|-----------------------|-------|-------|
|                          | LOW                   | MID   | HIGH  | LOW                   | MID   | HIGH  | LOW                   | MID   | HIGH  | LOW                   | MID   | HIGH  |
| Seat Tube Length (mm)    | 370                   |       |       | 390                   |       |       | 420                   |       |       | 450                   |       |       |
| Seat Tube Angle          | 76.2°   76.6°   77.0° |       |       | 76.2°   76.6°   77.0° |       |       | 77.3°   77.6°   78.0° |       |       | 77.3°   77.6°   78.0° |       |       |
| Top Tube Length (mm)     | 552                   | 552   | 550   | 567                   | 566   | 565   | 581                   | 580   | 579   | 603                   | 602   | 601   |
| Head Tube Length (mm)    | 95                    |       |       | 95                    |       |       | 100                   |       |       | 110                   |       |       |
| Head Tube Angle          | 64.7°   65.1°   65.5° |       |       | 64.6°   65.1°   65.5° |       |       | 64.8°   65.1°   65.5° |       |       | 64.8°   65.1°   65.5° |       |       |
| Fork Rake (mm)           | 44                    |       |       | 44                    |       |       | 44                    |       |       | 44                    |       |       |
| Trail (mm)               | 131                   | 127.9 | 124.8 | 131.6                 | 127.8 | 124.8 | 130.6                 | 127.7 | 124.8 | 130.5                 | 127.7 | 123.7 |
| Wheelbase (mm)           | 1166                  | 1166  | 1164  | 1183                  | 1180  | 1179  | 1208                  | 1207  | 1207  | 1232                  | 1231  | 1231  |
| Chain Stay Length (mm)   | 443                   | 442   | 440   | 443                   | 442   | 440   | 443                   | 442   | 440   | 443                   | 442   | 440   |
| Bottom Bracket Drop (mm) | 25                    | 20    | 15    | 24                    | 20    | 15    | 35                    | 30    | 25    | 35                    | 30    | 25    |
| Stack (mm)               | 629                   | 627   | 624   | 628                   | 627   | 624   | 628                   | 625   | 622   | 637                   | 634   | 631   |
| Reach (mm)               | 398                   | 402   | 406   | 413                   | 417   | 421   | 439                   | 442   | 447   | 459                   | 462   | 467   |
| Stand Over Height (mm)   | 727                   | 727   | 727   | 750                   | 750   | 750   | 760                   | 760   | 760   | 770                   | 770   | 770   |
| Stem Length (mm)         | 40                    |       |       | 50                    |       |       | 50                    |       |       | 50                    |       |       |
| Crank Length (mm)        | 165                   |       |       | 170                   |       |       | 170                   |       |       | 170                   |       |       |
| Wheel Size               | F29"/R27.5            |       |       | F29"/R27.5            |       |       | 29"                   |       |       | 29"                   |       |       |

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.