INTRIGUE LT ADVANCED PRO 0



SPECS

FRAME	
SIZES	XS, S: MX only, M, L: 29" F&R out of the box, MX compatible
COLORS	Mirage
FRAME	Advanced-Grade Composite front and rear triangles, 150mm Maestro Suspension, flip chip – Maestro 3, integrated down tube storage
FORK	Fox 36 Factory Live Valve, 160mm, FIT4 damper, Boost, 15x110, Kabolt, tapered, 44mm offset
SHOCK	Fox Factory Live 185x55, custom tuned for Liv
COMPONENTS	
HANDLEBAR	Giant Contact SLR TR35, composite, 35mm, 20mm rise XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPS	Liv Tactal Pro Single Lock-On XS and S: 110mm, M and L: 120mm
STEM	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
SEATPOST	TranzX travel-adjustable dropper, remote XS: 120-150mm travel / 30.9 x 459mm S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 140-170mm travel / 30.9 x 499mm
SADDLE	Liv Sylvia
PEDALS	platform
DRIVETRAIN	
SHIFTERS	SRAM AXS Rocker, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM XX1 Eagle AXS
BRAKES	Shimano XTR M9120, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
BRAKE LEVERS	Shimano XTR, BL-M9100
CASSETTE	SRAM XX1 Eagle AXS, 10x52
CHAIN	SRAM X01 Eagle
CRANKSET	SRAM XX1 Eagle DUB, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Zipp 3ZERO MOTO XS and S: [F] 29"", [R] 27.5"" M and L: [F] 29"", [R] 29"
HUBS	Zipp 3ZERO MOTO
SPOKES	Zipp 3ZERO MOTO
TIRES	[Size XS, S, M and L, F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [Size XS and S, R] Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless [Size M and L, R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	MRP AMg V2 chainguide, 3M tailgate protector, tubeless prepared, max tire size 2.5", max chainring size 32t, integrated down tube storage bag

Recommended Retail Price: $12,500.00

GEOMETRY

FRAME	M
	LOW | MID | HIGH
Seat Tube Length (inch)	16.5
Seat Tube Angle	77.3° | 77.6° | 78.0°
Top Tube Length (inch)	22.9 | 22.8 | 22.8
Head Tube Length (inch)	3.9
Head Tube Angle	64.8° | 65.1° | 65.5°
Fork Rake (inch)	1.7
Trail (inch)	5.1 | 5 | 4.9
Wheelbase (inch)	47.6 | 47.5 | 47.5
Chain Stay Length (inch)	17.4 | 17.4 | 17.3
Bottom Bracket Drop (inch)	1.4 | 1.2 | 1
Stack (inch)	24.7 | 24.6 | 24.5
Reach (inch)	17.3 | 17.4 | 17.6
Stand Over Height (inch)	29.9 | 29.9 | 29.9
Handlebar Width (inch)	29.9
Stem Length (inch)	2
Crank Length (inch)	6.7
Wheel Size	29"

**All specifications and prices listed are subject to change without notice.*
Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.