

# INTRIGUE LT ADVANCED PRO 0



## SPECIFIKACIJE

OKVIR	
VELIČINE	XS, S: MX only, M, L: 29" F&R out of the box, MX compatible
BOJE	Mirage
OKVIR	Advanced-Grade Composite front and rear triangles, 150mm Maestro Suspension, flip chip – Maestro 3, integrated down tube storage
VILICA	Fox 36 Factory Live Valve, 160mm, FIT4 damper, Boost, 15x110, Kabolt, tapered, 44mm offset
AMORTIZER	Fox Factory Live 185x55, custom tuned for Liv
KOMPONENTE	
VOLAN	Giant Contact SLR TR35, composite, 35mm, 20mm rise XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPS	Liv Tactal Pro Single Lock-On XS and S: 110mm, M and L: 120mm
LULA VOLANA	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
CIJEV SJEDALA	TranzX travel-adjustable dropper, remote XS: 120-150mm travel / 30.9 x 459mm S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 140-170mm travel / 30.9 x 499mm
SJEDALO	Liv Sylvia
PEDALE	platform
POGON	
RUČICE MJENJAČA	SRAM AXS Rocker, 1x12
PREDNJI MJENJAČ	N/A
STRAŽNJI MJENJAČ	SRAM XX1 Eagle AXS
KOČNICE	Shimano XTR M9120, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
RUČICE KOČNICA	Shimano XTR, BL-M9100
KAZETA	SRAM XX1 Eagle AXS, 10x52
LANAC	SRAM X01 Eagle
POGON	SRAM XX1 Eagle DUB, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
OSOVINA POGONA (BB)	SRAM DUB, press fit

KOTAČI	
OBRUČI	Zipp 3ZERO MOTO XS and S: [F] 29" [R] 27.5" M and L: [F] 29" [R] 29"
NABE	Zipp 3ZERO MOTO
ŽBICE	Zipp 3ZERO MOTO
GUME	[Size XS, S, M and L, F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [Size XS and S, R] Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless [Size M and L, R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
DODACI	MRP AMg V2 chainguide, 3M tailgate protector, tubeless prepared, max tire size 2.5", max chainring size 32t, integrated down tube storage bag

## GEOMETRIJA

OKVIR	XS			S		
	LOW	MID	HIGH	LOW	MID	HIGH
Dužina cijevi sjedala (mm)	370			390		
Kut cijevi sjedala	76,2°	76,6°	77,0°	76,2°	76,6°	77,0°
Dužina gornje cijevi (mm)	552	552	550	567	566	565
Dužina prednje cijevi (mm)	95			95		
Kut vilice	64,7°	65,1°	65,5°	64,6°	65,1°	65,5°
Zakrivljenost vilice (offset) (mm)	44			44		
Staza (mm)	131	127,9	124,8	131,6	127,8	124,8
Međuosovinski razmak kotača (mm)	1166	1166	1164	1183	1180	1179
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	443	442	440	443	442	440
Položaj osovine pogona (mm)	25	20	15	24	20	15
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	629	627	624	628	627	624
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	398	402	406	413	417	421
Prekoračna visina (mm)	727	727	727	750	750	750
Širina volana (mm)	760			760		
Dužina lule volana (mm)	40			50		
Dužina poluge pedale (mm)	165			170		
Veličina kotača	F29"/R27.5			F29"/R27.5		

Sve navedene specifikacije podložne su promjeni bez prethodne najave.