

INTRIGUE LT ADVANCED PRO 1 2023



SPECS

TELAIO	
TAGLIE	XS and S: MX only M and L: 29" F&R out of the box, MX compatible
COLORAZIONI	Raw Carbon/Chrome
TELAIO	Advanced-Grade Composite front and rear triangles, 150mm Maestro Suspension, flip chip - Maestro 3, integrated down tube storage
FORCELLA	Fox 36 Performance Elite, 160mm, Grip damper, Boost, 15x110, Kabolt, tapered, 44mm offset
AMMORTIZZATORE	Fox Float X Performance Elite 185x55, custom tuned for Liv
COMPONENTISTICA	
MANUBRIO	Giant Contact SLR TR35, composite, 35mm, 20mm rise XS: 760mm, S: 760mm, M: 760mm, L: 780mm
MANOPOLE	Liv Tactal Pro Single Lock-On XS and S: 110mm, M and L: 120mm
ATTACCO MANUBRIO	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
REGGISSELLA	TranzX travel-adjustable dropper, remote XS: 120-150mm travel / 30.9 x 459mm S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 140-170mm travel / 30.9 x 499mm
SELLA	Liv Sylvia
PEDALI	platform
SISTEMA DI TRASMISSIONE	
CAMBIO	SRAM GX Eagle, 1x12
DERAGLIATORE ANTERIORE	N/A
DERAGLIATORE POSTERIORE	SRAM GX Eagle
FRENI	SRAM G2 RSC, hydraulic, SRAM CenterLine rotors [F]200mm, [R]180mm
COMANDI FRENO	SRAM G2 RSC
PACCO PIGNONI	SRAM GX Eagle, 10x52
CATENA	SRAM GX
GUARNITURA	SRAM GX, 30t, 55mm chainline XS: 165mm, S:170mm, M:170mm, L:170mm
MOVIMENTO CENTRALE	SRAM DUB, press fit

RUOTE	
CERCHI	Giant TRX 2 29 WheelSystem, composite, 30mm inner width XS and S: [F] 29", [R] 27.5" M and L: [F] 29", [R] 29"
MOZZI	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 3-pawl driver, 6-bolt
RAGGI	Sapim
COPERTONI	[Size XS, S, M and L, F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [Size XS and S, R] Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless [Size M and L, R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRA	MRP AMg V2 chainguide, 3M tailgate protector, tubeless prepared, max tire size 2.5", max chainring size 32t, integrated down tube storage bag

Prezzo: € 7.099

GEOMETRIA

TELAIO	XS			S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Lunghezza Tubo Sella (mm)	370			390			420			450		
Angolo Tubo Sella	76,2° 76,6° 77,0°			76,2° 76,6° 77,0°			77,3° 77,6° 78,0°			77,3° 77,6° 78,0°		
Lunghezza Tubo Orizzontale (mm)	552	552	550	567	566	565	581	580	579	603	602	601
Lunghezza Tubo Sterzo (mm)	95			95			100			110		
Angolo Sterzo	64,7° 65,1° 65,5°			64,6° 65,1° 65,5°			64,8° 65,1° 65,5°			64,8° 65,1° 65,5°		
Rake Forcella (mm)	44			44			44			44		
Avancorsa (mm)	131	127,9	124,8	131,6	127,8	124,8	130,6	127,7	124,8	130,5	127,6	124,7
Interasse (mm)	1166	1166	1164	1183	1180	1179	1208	1207	1207	1232	1232	1232
Lunghezza Carro Posteriore (mm)	443	442	440	443	442	440	443	442	440	443	442	441
Drop Movimento Centrale (mm)	25	20	15	24	20	15	35	30	25	35	30	25
Stack (mm)	629	627	624	628	627	624	628	625	622	637	634	631
Reach (mm)	398	402	406	413	417	421	439	442	447	459	462	465
Altezza stand over (mm)	727	727	727	750	750	750	760	760	760	770	770	770
Larghezza Manubrio c/c (mm)	760			760			760			780		
Lunghezza Attacco Manubrio (mm)	40			50			50			50		
Lunghezza Pedivella (mm)	165			170			170			170		
Dimensione Ruote	F29"/R27.5			F29"/R27.5			29"			29"		

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.