INTRIGUE LT ADVANCED PRO 1



SPECS

FRAME	
SIZES	XS and S: MX only M and L: 29"" F&R out of the box, MX compatible
COLORS	Raw Carbon/Chrome
FRAME	Advanced-Grade Composite front and rear triangles, 150mm Maestro Suspension, flip chip – Maestro 3, integrated down tube storage
FORK	Fox 36 Performance Elite, 160mm, Grip damper, Boost, 15x110, Kabolt, tapered, 44mm offset
SHOCK	Fox Float X Performance Elite 185x55, custom tuned for Liv
COMPONENTS	
HANDLEBAR	Giant Contact SLR TR35, composite, 35mm, 20mm rise XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPS	Liv Tactal Pro Single Lock-On XS and S: 110mm, M and L: 120mm
STEM	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
SEATPOST	TranzX travel-adjustable dropper, remote XS: 120-150mm travel / 30.9 x 459mm S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 140-170mm travel / 30.9 x 499mm
SADDLE	Liv Sylvia
PEDALS	platform
DRIVETRAIN	
SHIFTERS	SRAM GX Eagle, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM GX Eagle
BRAKES	SRAM G2 RSC, hydraulic, SRAM CenterLine rotors [F]200mm, [R]180mm
BRAKE LEVERS	SRAM G2 RSC
CASSETTE	SRAM GX Eagle, 10x52
CHAIN	SRAM GX
CRANKSET	SRAM GX, 30t, 55mm chainline XS: 165mm, S:170mm, M:170mm, L:170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant TRX 2 29 WheelSystem, composite, 30mm inner width XS and S: [F] 29"", [R] 27.5"" M and L: [F] 29"", [R] 29"
HUBS	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 3-pawl driver, 6-bolt
SPOKES	Sapim
TIRES	[Size XS, S, M and L, F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [Size XS and S, R] Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless [Size M and L, R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	MRP AMg V2 chainguide, 3M tailgate protector, tubeless prepared, max tire size 2.5", max chainring size 32t, integrated down tube storage bag

Price: ₹ 7,100.00

GEOMETRY

FRAME	XS	S	M	L
	LOW | MID | HIGH	LOW | MID | HIGH	LOW | MID | HIGH	LOW | MID | HIGH
Seat Tube Length (mm)	370	390	420	450
Seat Tube Angle	76.2° | 76.6° | 77.0°	76.2° | 76.6° | 77.0°	77.3° | 77.6° | 78.0°	77.3° | 77.6° | 78.0
Top Tube Length (mm)	552 | 552 | 550	567 | 566 | 565	581 | 580 | 579	603 | 602 | 601
Head Tube Length (mm)	95	95	100	110
Head Tube Angle	64.7° | 65.1° | 65.5°	64.6° | 65.1° | 65.5°	64.8° | 65.1° | 65.5°	64.8° | 65.1° | 65.5
Fork Rake (mm)	44	44	44	44
Trail (mm)	131 | 127.9 | 124.8	131.6 | 127.8 | 124.8	130.6 | 127.7 | 124.8	130.5 | 127.7 | 124
Wheelbase (mm)	1166 | 1166 | 1164	1183 | 1180 | 1179	1208 | 1207 | 1207	1232 | 1231 | 1231
Chain Stay Length (mm)	443 | 442 | 440	443 | 442 | 440	443 | 442 | 440	443 | 442 | 440
Bottom Bracket Drop (mm)	25 | 20 | 15	24 | 20 | 15	35 | 30 | 25	35 | 30 | 25
Stack (mm)	629 | 627 | 624	628 | 627 | 624	628 | 625 | 622	637 | 634 | 631
Reach (mm)	398 | 402 | 406	413 | 417 | 421	439 | 442 | 447	459 | 462 | 467
Stand Over Height (mm)	727 | 727 | 727	750 | 750 | 750	760 | 760 | 760	770 | 770 | 770
Handlebar Width (mm)	760	760	760	780
Stem Length (mm)	40	50	50	50
Crank Length (mm)	165	170	170	170
Wheel Size	F29"/R27.5	F29"/R27.5	29"	29"

The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city / country.