

# INTRIGUE LT ADVANCED PRO 1



## SPECS

FRAME	
<b>SIZES</b>	XS and S: MX only M and L: 29" F&R out of the box, MX compatible
<b>COLORS</b>	Raw Carbon/Chrome
<b>FRAME</b>	Advanced-Grade Composite front and rear triangles, 150mm Maestro Suspension, flip chip – Maestro 3, integrated down tube storage
<b>FORK</b>	Fox 36 Performance Elite, 160mm, Grip damper, Boost, 15x110, Kabolt, tapered, 44mm offset
<b>SHOCK</b>	Fox Float X Performance Elite 185x55, custom tuned for Liv
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact SLR TR35, composite, 35mm, 20mm rise XS: 760mm, S: 760mm, M: 760mm, L: 780mm
<b>GRIPS</b>	Liv Tactal Pro Single Lock-On XS and S: 110mm, M and L: 120mm
<b>STEM</b>	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
<b>SEATPOST</b>	TranzX travel-adjustable dropper, remote XS: 120-150mm travel / 30.9 x 459mm S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 140-170mm travel / 30.9 x 499mm
<b>SADDLE</b>	Liv Sylvia
<b>PEDALS</b>	platform
DRIVETRAIN	
<b>SHIFTERS</b>	SRAM GX Eagle, 1x12
<b>FRONT DERAILLEUR</b>	N/A
<b>REAR DERAILLEUR</b>	SRAM GX Eagle
<b>BRAKES</b>	SRAM G2 RSC, hydraulic, SRAM CenterLine rotors [F]200mm, [R]180mm
<b>BRAKE LEVERS</b>	SRAM G2 RSC
<b>CASSETTE</b>	SRAM GX Eagle, 10x52
<b>CHAIN</b>	SRAM GX
<b>CRANKSET</b>	SRAM GX, 30t, 55mm chainline XS: 165mm, S:170mm, M:170mm, L:170mm
<b>BOTTOM BRACKET</b>	SRAM DUB, press fit

WHEELS	
<b>RIMS</b>	Giant TRX 2 29 WheelSystem, composite, 30mm inner width XS and S: [F] 29", [R] 27.5" M and L: [F] 29", [R] 29"
<b>HUBS</b>	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 3-pawl driver, 6-bolt
<b>SPOKES</b>	Sapim
<b>TIRES</b>	[Size XS, S, M and L, F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [Size XS and S, R] Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless [Size M and L, R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
<b>EXTRAS</b>	MRP AMg V2 chainguide, 3M tailgate protector, tubeless prepared, max tire size 2.5", max chainring size 32t, integrated down tube storage bag

## GEOMETRY

FRAME	XS			S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	370			390			420			450		
Seat Tube Angle	76,2°	76,6°	77,0°	76,2°	76,6°	77,0°	77,3°	77,6°	78,0°	77,3°	77,6°	78,0°
Top Tube Length (mm)	552	552	550	567	566	565	581	580	579	603	602	601
Head Tube Length (mm)	95			95			100			110		
Head Tube Angle	64,7°	65,1°	65,5°	64,6°	65,1°	65,5°	64,8°	65,1°	65,5°	64,8°	65,1°	65,5°
Fork Rake (mm)	44			44			44			44		
Trail (mm)	131	127,9	124,8	131,6	127,8	124,8	130,6	127,7	124,8	130,5	127,7	124,8
Wheelbase (mm)	1166	1166	1164	1183	1180	1179	1208	1207	1207	1232	1231	1231
Chain Stay Length (mm)	443	442	440	443	442	440	443	442	440	443	442	440
Bottom Bracket Drop (mm)	25	20	15	24	20	15	35	30	25	35	30	25
Stack (mm)	629	627	624	628	627	624	628	625	622	637	634	631
Reach (mm)	398	402	406	413	417	421	439	442	447	459	462	467
Stand Over Height (mm)	727	727	727	750	750	750	760	760	760	770	770	770
Handlebar Width (mm)	760			760			760			780		
Stem Length (mm)	40			50			50			50		
Crank Length (mm)	165			170			170			170		
Wheel Size	F29"/R27.5			F29"/R27.5			29"			29"		

All specifications listed are subject to change without notice.