

INTRIGUE LT ADVANCED PRO 1



TECHNIQUES

CADRE	
TAILLES	XS and S: MX only M and L: 29" F&R out of the box, MX compatible
COLORIS	Raw Carbon/Chrome
CADRE	Advanced-Grade Composite front and rear triangles, 150mm Maestro Suspension, flip chip - Maestro 3, integrated down tube storage
FOURCHE	Fox 36 Performance Elite, 160mm, Grip damper, Boost, 15x110, Kabolt, tapered, 44mm offset
AMORTISSEUR	Fox Float X Performance Elite 185x55, custom tuned for Liv
COMPOSANTS	
CINTRE	Giant Contact SLR TR35, composite, 35mm, 20mm rise XS: 760mm, S: 760mm, M: 760mm, L: 780mm
POIGNÉES	Liv Tactal Pro Single Lock-On XS and S: 110mm, M and L: 120mm
POTENCE	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
TIGE DE SELLE	TranzX travel-adjustable dropper, remote XS: 120-150mm travel / 30.9 x 459mm S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 140-170mm travel / 30.9 x 499mm
SELLE	Liv Sylvia
PÉDALES	platform
DÉRAILLEUR	
MANETTES	SRAM GX Eagle, 1x12
DÉRAILLEUR AVANT	N/A
DÉRAILLEUR ARRIÈRE	SRAM GX Eagle
FREINS	SRAM G2 RSC, hydraulic, SRAM CenterLine rotors [F]200mm, [R]180mm
LEVIER DE FREIN	SRAM G2 RSC
CASSETTE	SRAM GX Eagle, 10x52
CHAÎNE	SRAM GX
PÉDALIER	SRAM GX, 30t, 55mm chainline XS: 165mm, S:170mm, M:170mm, L:170mm
BOITIER DE PÉDALIER	SRAM DUB, press fit

ROUES	
JANTES	Giant TRX 2 29 WheelSystem, composite, 30mm inner width XS and S: [F] 29", [R] 27.5" M and L: [F] 29", [R] 29"
MOYEURS	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 3-pawl driver, 6-bolt
RAYONS	Sapim
PNEUS	[Size XS, S, M and L, F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [Size XS and S, R] Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless [Size M and L, R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	MRP AMg V2 chainguide, 3M tailgate protector, tubeless prepared, max tire size 2.5", max chainring size 32t, integrated down tube storage bag
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles

Prix Public Conseillé: 7 100,00 €

GÉOMÉTRIE

CADRE	XS			S			M		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Longueur de tube de selle (mm)	370			390			420		
Angle de tube de selle	76,2° 76,6° 77,0°			76,2° 76,6° 77,0°			77,3° 77,6° 78,0°		
Longueur du tube supérieur (mm)	552	552	550	567	566	565	581	580	579
Longueur du tube de direction (mm)	95			95			100		
Angle du tube de direction	64,7° 65,1° 65,5°			64,6° 65,1° 65,5°			64,8° 65,1° 65,5°		
Déport de fourche (mm)	44			44			44		
Trail (mm)	131	127,9	124,8	131,6	127,8	124,8	130,6	127,7	124,8
Empattement (mm)	1166	1166	1164	1183	1180	1179	1208	1207	1207
Longueur des bases (mm)	443	442	440	443	442	440	443	442	440
Drop du boîtier de pédalier (mm)	25	20	15	24	20	15	35	30	25
Stack (mm)	629	627	624	628	627	624	628	625	622
Reach (mm)	398	402	406	413	417	421	439	442	447
Hauteur en statique (mm)	727	727	727	750	750	750	760	760	760
Largeur de cintre (mm)	760			760			760		
Longueur de potence (mm)	40			50			50		
Longueur des manivelles (mm)	165			170			170		
Diamètre des roues	F29"/R27.5			F29"/R27.5			29"		

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.