



INTRIGUE LT ADVANCED PRO 1



SPECS

QUADRO	
TAMANHOS	XS and S: MX only M and L: 29" F&R out of the box, MX compatible
CORES	Raw Carbon/Chrome
QUADRO	Advanced-Grade Composite front and rear triangles, 150mm Maestro Suspension, flip chip - Maestro 3, integrated down tube storage
FORQUILHA	Fox 36 Performance Elite, 160mm, Grip damper, Boost, 15x110, Kabolt, tapered, 44mm offset
AMORTECEDORES	Fox Float X Performance Elite 185x55, custom tuned for Liv
COMPONENTES	
GUIADOR	Giant Contact SLR TR35, composite, 35mm, 20mm rise XS: 760mm, S: 760mm, M: 760mm, L: 780mm
PUNHOS	Liv Tactal Pro Single Lock-On XS and S: 110mm, M and L: 120mm
AVANÇO	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
ESPIÃO DE SELIM	TranzX travel-adjustable dropper, remote XS: 120-150mm travel / 30.9 x 459mm S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 140-170mm travel / 30.9 x 499mm
SELIM	Liv Sylvia
PEDAIS	platform
TRANSMISSÃO	
MANETES	SRAM GX Eagle, 1x12
DESVIADOR DIANTEIRO	N/A
DESVIADOR TRASEIRO	SRAM GX Eagle
TRAVÕES	SRAM G2 RSC, hydraulic, SRAM CenterLine rotors [F]200mm, [R]180mm
MANÍPULOS DOS TRAVÕES	SRAM G2 RSC
CASSETTE	SRAM GX Eagle, 10x52
CORRENTE	SRAM GX
CONJUNTO PEDALEIRO	SRAM GX, 30t, 55mm chainline XS: 165mm, S:170mm, M:170mm, L:170mm
MOVIMENTO CENTRAL	SRAM DUB, press fit

RODAS	
AROS	Giant TRX 2 29 WheelSystem, composite, 30mm inner width XS and S: [F] 29", [R] 27.5" M and L: [F] 29", [R] 29"
CUBOS	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 3-pawl driver, 6-bolt
RAIOS	Sapim
PNEUS	[Size XS, S, M and L, F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [Size XS and S, R] Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless [Size M and L, R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	MRP AMg V2 chainguide, 3M tailgate protector, tubeless prepared, max tire size 2.5", max chainring size 32t, integrated down tube storage bag

Preço: 6 199,00 €

GEOMETRIA

QUADRO	XS
	LOW MID HIGH
Comprimento do tubo do assento (mm)	370
Ângulo do tubo do assento	76,2° 76,6° 77,0°
Comprimento do tubo superior (mm)	552 552 550
Comprimento do tubo principal (mm)	95
Ângulo do tubo principal	64,7° 65,1° 65,5°
Garfo ancinho (mm)	44
Trilha (mm)	131 127,9 124,8
distância entre eixos (mm)	1166 1166 1164
Comprimento Chain Stay (mm)	443 442 440
Suporte inferior (mm)	25 20 15
Pilha (mm)	629 627 624
Alcançar (mm)	398 402 406
Altura do standover (mm)	727 727 727
Largura do guidão (mm)	760
Comprimento da haste (mm)	40
Comprimento da Manivela (mm)	165
Tamanho da roda	F29"/R27.5

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.