

INTRIGUE LT ADVANCED PRO 1



ŠPECIFIKÁCIE

RÁM	
VELKOSTI	XS and S: MX only M and L: 29" F&R out of the box, MX compatible
FARBY	Raw Carbon/Chrome
RÁM	Advanced-Grade Composite front and rear triangles, 150mm Maestro Suspension, flip chip – Maestro 3, integrated down tube storage
VIDLICA	Fox 36 Performance Elite, 160mm, Grip damper, Boost, 15x110, Kabolt, tapered, 44mm offset
TLMIČ	Fox Float X Performance Elite 185x55, custom tuned for Liv
KOMPONENTY	
RIADIDLÁ	Giant Contact SLR TR35, composite, 35mm, 20mm rise XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPY	Liv Tactal Pro Single Lock-On XS and S: 110mm, M and L: 120mm
PREDSTAVEC	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
SEDLOVKA	TranzX travel-adjustable dropper, remote XS: 120-150mm travel / 30.9 x 459mm S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 140-170mm travel / 30.9 x 499mm
SEDADLO	Liv Sylvia
PEDÁLE	platform
POHON	
RADENIE	SRAM GX Eagle, 1x12
PREŠMYKAČ	N/A
PREHADZOVAČKA	SRAM GX Eagle
BRZDY	SRAM G2 RSC, hydraulic, SRAM CenterLine rotors [F]200mm, [R]180mm
BRZDOVÉ PÁKY	SRAM G2 RSC
KAZETA	SRAM GX Eagle, 10x52
REŤAZ	SRAM GX
KLUKY	SRAM GX, 30t, 55mm chainline XS: 165mm, S:170mm, M:170mm, L:170mm
STREDOVÉ ZLOŽENIE	SRAM DUB, press fit

KOLESÁ	
RÁFIKY	Giant TRX 2 29 WheelSystem, composite, 30mm inner width XS and S: [F] 29", [R] 27.5" M and L: [F] 29", [R] 29"
NÁBOJE	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 3-pawl driver, 6-bolt
ŠPICE	Sapim
PNEUMATIKY	[Size XS, S, M and L, F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [Size XS and S, R] Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless [Size M and L, R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
DOPLNKY	MRP AMg V2 chainguide, 3M tailgate protector, tubeless prepared, max tire size 2.5", max chainring size 32t, integrated down tube storage bag

Cena: 7 199 €

GEOMETRIA

RÁM	XS			S			M		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Dĺžka sedlovej trubky (mm)	370			390			420		
Uhol sedlovej trubky	76,2°	76,6°	77,0°	76,2°	76,6°	77,0°	77,3°	77,6°	78,0°
Dĺžka hornej rámovej trubky (mm)	552	552	550	567	566	565	581	580	579
Dĺžka hlavovej trubky (mm)	95			95			100		
Uhol hlavovej trubky	64,7°	65,1°	65,5°	64,6°	65,1°	65,5°	64,8°	65,1°	65,5°
Offset vidlice (mm)	44			44			44		
Trail (mm)	131	127,9	124,8	131,6	127,8	124,8	130,6	127,7	124,8
Rázvor (mm)	1166	1166	1164	1183	1180	1179	1208	1207	1207
Dĺžka zadnej stavby (mm)	443	442	440	443	442	440	443	442	440
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	25	20	15	24	20	15	35	30	25
Stack - výška riadenia (mm)	629	627	624	628	627	624	628	625	622
Reach (mm)	398	402	406	413	417	421	439	442	447
Výška rámu od zeme (mm)	727	727	727	750	750	750	760	760	760
Šírka riaditok (mm)	760			760			760		
Dĺžka predstavca (mm)	40			50			50		
Dĺžka klúku (mm)	165			170			170		
Rozmer kolies	F29"/R27.5			F29"/R27.5			29"		

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.