

INTRIGUE LT ADVANCED PRO 1



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS and S: MX only M and L: 29" F&R out of the box, MX compatible
BARVE	Raw Carbon/Chrome
OKVIR	Advanced-Grade Composite front and rear triangles, 150mm Maestro Suspension, flip chip – Maestro 3, integrated down tube storage
VILICE	Fox 36 Performance Elite, 160mm, Grip damper, Boost, 15x110, Kabolt, tapered, 44mm offset
AMORTIZER	Fox Float X Performance Elite 185x55, custom tuned for Liv
KOMPONENTE	
KRMILO	Giant Contact SLR TR35, composite, 35mm, 20mm rise XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPS	Liv Tactal Pro Single Lock-On XS and S: 110mm, M and L: 120mm
OPORA KRMILA	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
OPORA SEDEŽA	TranzX travel-adjustable dropper, remote XS: 120-150mm travel / 30.9 x 459mm S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 140-170mm travel / 30.9 x 499mm
SEDEŽ	Liv Sylvia
PEDALA	platform
POGON	
PRESTAVNE ROČICE	SRAM GX Eagle, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM GX Eagle
ZAVORE	SRAM G2 RSC, hydraulic, SRAM CenterLine rotors [F]200mm, [R]180mm
ZAVORNE ROČICE	SRAM G2 RSC
VERIŽNIK	SRAM GX Eagle, 10x52
VERIGA	SRAM GX
GONILKE Z VERIŽNIKI	SRAM GX, 30t, 55mm chainline XS: 165mm, S:170mm, M:170mm, L:170mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant TRX 2.29 WheelSystem, composite, 30mm inner width XS and S: [F] 29", [R] 27.5" M and L: [F] 29", [R] 29"
PESTA	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 3-pawl driver, 6-bolt
NAPERE	Sapim
PLAŠČI	[Size XS, S, M and L, F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [Size XS and S, R] Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless [Size M and L, R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
DODATKI	MRP AMg V2 chainguide, 3M tailgate protector, tubeless prepared, max tire size 2.5", max chainring size 32t, integrated down tube storage bag

GEOMETRIJA

OKVIR	XS			S			M			L
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	L
Dolžina sedežne cevi (mm)	370			390			420			4
Kot sedežne cevi	76,2°	76,6°	77,0°	76,2°	76,6°	77,0°	77,3°	77,6°	78,0°	7
Top Tube Length (mm)	552	552	550	567	566	565	581	580	579	6
Višina glave okvirja (mm)	95			95			100			1
Krmilni kot	64,7°	65,1°	65,5°	64,6°	65,1°	65,5°	64,8°	65,1°	65,5°	6
Zamik vpetja osi (mm)	44			44			44			4
Trail (mm)	131	127,9	124,8	131,6	127,8	124,8	130,6	127,7	124,8	1
Medosna razdalja (mm)	1166	1166	1164	1183	1180	1179	1208	1207	1207	1
Dolžina cevi ob verigi (mm)	443	442	440	443	442	440	443	442	440	4
Bottom Bracket Drop (mm)	25	20	15	24	20	15	35	30	25	3
Oddaljenost zgornje cevi od gonilne osi (mm)	629	627	624	628	627	624	628	625	622	6
Doseg (mm)	398	402	406	413	417	421	439	442	447	4
Višina zgornje cevi (mm)	727	727	727	750	750	750	760	760	760	7
Širina krmila (mm)	760			760			760			7
Dolžina opore krmila (mm)	40			50			50			5
Dolžina gonilke (mm)	165			170			170			1
Velikost obročnikov	F29"/R27.5			F29"/R27.5			29"			2

Vse navedene specifikacije se lahko spremenijo brez obvestila.