

# INTRIGUE LT ADVANCED PRO 2



## SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS and S: MX only M and L: 29" F&R out of the box, MX compatible
BARVE	Mushroom
OKVIR	Advanced-Grade Composite front and rear triangles, 150mm Maestro Suspension, flip chip – Maestro 3, integrated down tube storage
VILICE	Marzocchi Bomber Z1, 160mm, Rail damper, Boost, 15x110, Kabolt, tapered, 44mm offset
AMORTIZER	Fox Float DPS Performance 185x55, custom tuned for Liv
KOMPONENTE	
KRMILO	Giant Contact SL TR35, 35mm, 20mm rise XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPS	Liv Tactal Pro Single Lock-On XS and S: 110mm, M and L: 120mm
OPORA KRMILA	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
OPORA SEDEŽA	TranzX travel-adjustable dropper, remote XS: 120-150mm travel / 30.9 x 459mm S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 140-170mm travel / 30.9 x 499mm
SEDEŽ	Liv Sylvia
PEDALA	platform
POGON	
PRESTAVNE ROČICE	SRAM SX Eagle, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM SX Eagle
ZAVORE	Tektro M745, hydraulic, Tektro rotors [F]203mm, [R]180mm
ZAVORNE ROČICE	Tektro
VERIŽNIK	SRAM SX Eagle, 11x50
VERIGA	SRAM SX Eagle
GONILKE Z VERIŽNIKI	SRAM SX, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant TR 1 29 WheelSystem, alloy, 30mm inner width XS and S: [F] 29", [R] 27.5" M and L: [F] 29", [R] 29"
PESTA	alloy, sealed bearing
NAPERE	Sapim
PLAŠČI	[Size XS, S, M and L, F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [Size XS and S, R] Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless [Size M and L, R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
DODATKI	MRP AMg V2 chainguide, 3M tailgate protector, tubeless prepared, max tire size 2.5", max chainring size 32t, integrated down tube storage bag

## GEOMETRIJA

OKVIR	XS			S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Dolžina sedežne cevi (mm)	370			390			420			440		
Kot sedežne cevi	76,2°   76,6°   77,0°			76,2°   76,6°   77,0°			77,3°   77,6°   78,0°			77,6°   78,0°   78,4°		
Top Tube Length (mm)	552   552   550			567   566   565			581   580   579			596   595   594		
Višina glave okvirja (mm)	95			95			100			100		
Krmilni kot	64,7°   65,1°   65,5°			64,6°   65,1°   65,5°			64,8°   65,1°   65,5°			65,1°   65,5°   65,9°		
Zamik vpetja osi (mm)	44			44			44			44		
Trail (mm)	131   127,9   124,8			131,6   127,8   124,8			130,6   127,7   124,8			129,6   126,7   123,8		
Medosna razdalja (mm)	1166   1166   1164			1183   1180   1179			1208   1207   1207			1233   1232   1232		
Dolžina cevi ob verigi (mm)	443   442   440			443   442   440			443   442   440			443   442   440		
Bottom Bracket Drop (mm)	25   20   15			24   20   15			35   30   25			35   30   25		
Oddaljenost zgornje cevi od gonilne osi (mm)	629   627   624			628   627   624			628   625   622			628   625   622		
Doseg (mm)	398   402   406			413   417   421			439   442   447			464   467   474		
Višina zgornje cevi (mm)	727   727   727			750   750   750			760   760   760			770   770   770		
Širina krmila (mm)	760			760			760			760		
Dolžina opore krmila (mm)	40			50			50			50		
Dolžina gonilke (mm)	165			170			170			170		
Velikost obročnikov	F29"/R27.5			F29"/R27.5			29"			29"		

Vse navedene specifikacije se lahko spremenijo brez obvestila.