

INTRIGUE LT



SPECS

FRAME	
SIZES	XS, S: MX only, M, L: 29" F&R out of the box, MX compatible
COLOURS	Soap Suds
FRAME	ALUXX SL-grade aluminum front and rear triangles, 150mm Maestro Suspension, flip chip - Maestro 3, 12x148mm thru-axle, integrated down tube storage
FORK	Marzocchi Bomber Z1, 170mm, Rail damper, Boost 15x110 Kabolt, tapered, 44mm offset
SHOCK	Fox Float Performance 185x55, custom tuned for Liv, recommended sag 30%
COMPONENTS	
HANDLEBAR	Giant Contact TR35, alloy, 35mm, 20mm rise XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPS	Liv Tactal Pro Single Lock-On XS/S: 120mm, M/L: 130mm
STEM	Giant Contact SL 35 XS: 40mm, S: 50mm, M: 50mm, L: 50mm
SEATPOST	Giant Contact Switch AT dropper, remote XS: 140-170mm travel/ 30.9x470mmS: 140-170mm travel/ 30.9x470mmM: 170-200mm travel/30.9x530mmL: 170-200mm travel/30.9x530mm
SADDLE	Liv Sylvia
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano Deore, M6100, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano Deore, Shadow +
BRAKES	Shimano BR-MT420, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
BRAKE LEVERS	Shimano BL-MT401
CASSETTE	Shimano Deore M6100, 10x51
CHAIN	KMC X12
CRANKSET	Praxis Cadet M24 Boost, steel chain ring 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	Praxis, press fit

WHEELS	
RIMS	Giant TRA 2 wheelset, 6061 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
HUBS	[F] Giant MTB alloy, six-bolt, [R] Giant MTB alloy, 72 POE (Points of Engagement), six-bolt, MicroSpline driver body
SPOKES	Sapim, 28, J-bend
TIRES	Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	MRP AMG CS chain guide, 3M tailgate protector, tubeless prepared, integrated down tube storage bag, max tire size 2.5", max chainring size 32t

Suggested Retail Price (CDN): \$3,799.00

FRAME GEOMETRY

FRAME	XS			S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	370			390			420			450		
Seat Post Insertion Depth (mm)	230			250			280			310		
Seat Tube Angle	76.2°	76.6°	77.0°	76.2°	76.6°	77.0°	77.3°	77.6°	78.0°	77.3°	77.6°	
Top Tube Length (mm)	552	552	550	567	566	565	581	580	579	603	602	60
Head Tube Length (mm)	95			95			100			110		
Head Tube Angle	64.7°	65.1°	65.5°	64.6°	65.1°	65.5°	64.8°	65.1°	65.5°	64.8°	65.1°	
Fork Rake (mm)	44			44			44			44		
Trail (mm)	131	127.9	124.8	131.6	127.8	124.8	130.6	127.7	124.8	130.5	127.7	
Wheelbase (mm)	1166	1166	1164	1183	1180	1179	1208	1207	1207	1232	1231	
Chain Stay Length (mm)	443	442	440	443	442	440	443	442	440	443	442	44
Bottom Bracket Drop (mm)	25	20	15	24	20	15	35	30	25	35	30	25
Stack (mm)	629	627	624	628	627	624	628	625	622	637	634	63
Reach (mm)	398	402	406	413	417	421	439	442	447	459	462	46
Stand Over Height (mm)	613	613	613	674	674	674	712	712	712	750	750	75
Handlebar Width (mm)	760			760			760			780		
Stem Length (mm)	40			50			50			50		
Crank Length (mm)	165			170			170			170		
Wheel Size	F 29 R 27.5			F 29 R 27.5			29"			29"		

All prices and specifications are subject to change without notice.