

INTRIGUE X 1



SPECS

FRAME	
SIZES	XS, S, M, L
COLOURS	Gloss Black Diamond/Matte Black
FRAME	ALUXX SL-grade aluminium front and rear triangles, 140mm Maestro Suspension, flip chip - Maestro 3, flip chip - headset, integrated down tube storage
FORK	Fox 36 Float Performance, 150mm, Grip damper, Boost 15x110 Kabolt X, tapered, 44mm offset
SHOCK	Fox Float Performance, 185x52.5, custom tuned for Liv
COMPONENTS	
HANDLEBAR	Giant Contact TR35, 20mm rise, alloy
GRIPS	Liv Tactal Pro Single Lock-on
STEM	Giant Contact SL, 35mm
SEATPOST	Giant Contact Switch, adjustable dropper, remote XS&S: 140-170mm travel / 30.9 x 470mm M&L: 170-200mm travel / 30.9 x 530mm
SADDLE	Liv Sylvia
PEDALS	PEDALS NOT SUPPLIED
DRIVETRAIN	
SHIFTERS	Shimano SLX M7100, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano SLX M7100, Shadow +
BRAKES	Shimano BR-MT520, hydraulic, Shimano RT-66 [F] 203mm, [R] 180mm
BRAKE LEVERS	Shimano BL-MT501
CASSETTE	Shimano SLX M7100, 10x51
CHAIN	KMC X12
CRANKSET	Shimano MT512-1, 30t, 55mm chainline
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant TRA, 29" hookless aluux wheelsystem, 30mm inner width, 40mm outer width, 21mm H,72t POE, 28 SP spokes, DBL technology, MS driver body
HUBS	alloy, sealed bearing
SPOKES	Sapim
TYRES	Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	3M tailgate protector, factory tubeless set up, integrated down tube storage bag, max tyre size 2.5", max chainring size 34t

Price: €4,599.00

GEOMETRY

FRAME	XS			S			M		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	370			390			420		
Seat Post Insertion Depth (mm)	240			260			290		
Seat Tube Angle	76.2° 76.6° 76.9°			76.2° 76.6° 76.9°			76.8° 77.2° 77.5°		
Top Tube Length (mm)	548 547 546			564 563 562			582 581 580		
Head Tube Length (mm)	95			100			105		
Head Tube Angle	64.4° 64.8° 65.1°			64.4° 64.8° 65.1°			64.4° 64.8° 65.1°		
Fork Rake (mm)	44			44			44		
Trail (mm)	134.2 131.3 128.3			134.1 131.3 128.3			134.1 131.3 128.3		
Wheelbase (mm)	1159 1159 1158			1176 1176 1175			1202 1201 1201		
Chain Stay Length (mm)	440 439 438			440 439 438			440 439 438		
Bottom Bracket Drop (mm)	25 20 15			25 20 15			40 35 30		
Stack (mm)	615 613 610			620 617 614			621 619 616		
Reach (mm)	397 401 405			412 415 420			436 440 444		
Stand Over Height (mm)	730 734 738			733 737 742			745 749 754		
Handlebar Width (mm)	760			760			760		
Stem Length (mm)	40			50			50		
Crank Length (mm)	165			170			170		
Wheel Size	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

All specifications listed are subject to change without notice.