

INTRIGUE X 1



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, L
COLORES	Gloss Black Diamond/Matte Black
CUADRO	ALUXX SL-grade aluminum front and rear triangles, 140mm Maestro Suspension, flip chip - Maestro 3, flip chip - headset, integrated down tube storage
HORQUILLA	Fox 36 Float Performance, 150mm, Grip damper, Boost 15x110 Kabolt X, tapered, 44mm offset
AMORTIGUADOR	Fox Float Performance, 185x52.5, custom tuned for Liv
COMPONENTES	
MANILLAR	Giant Contact TR35, 20mm rise, alloy XS: 760mm, S: 760mm, M: 760mm, L: 780mm
PUÑOS	Liv Tactal Pro Single Lock-on XS/S: 120mm M/L: 130mm
POTENCIA	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
TIJA DE SILLÍN	Giant Contact Switch, adjustable dropper, remote XS: 140-170mm travel / 30.9 x 470mm S: 140-170mm travel / 30.9 x 470mm M: 170-200mm travel / 30.9 x 530mm L: 170-200mm travel / 30.9 x 530mm
SILLÍN	Liv Sylvia
PEDALES	platform
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano SLX M7100, 1x12
DESVIADOR	N/A
CAMBIO TRASERO	Shimano SLX M7100, Shadow +
FRENOS	Shimano BR-MT520, hydraulic, Shimano RT-66 [F] 203mm, [R] 180mm
PALANCAS DE FRENOS	Shimano BL-MT501
CASSETTE	Shimano SLX M7100, 10x51
CADENA	KMC X12
JGO. PLATOS Y BIELAS	Shimano MT512-1, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
CAJA DE PEDALIER	Shimano, press fit

RUEDAS	
LLANTAS	Giant TR alloy WheelSystem, 30mm rim inner width XS/S: [F] 29, [R] 27.5 M/L: [F] 29, [R] 29
BUJES	alloy, sealed bearing
RADIOS	Sapim
CUBIERTAS	Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	3M tailgate protector, tubeless prepared, integrated down tube storage bag, max tire size 2.5", max chainring size 34t

Precio: 4.799,00 €

GEOMETRÍA

CUADRO	XS			S			M			L
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	
Longitud del tubo del sillín (mm)	370			390			420			451
Seat Post Insertion Depth (mm)	240			260			290			321
Ángulo del tubo del sillín	76,2°	76,6°	76,9°	76,2°	76,6°	76,9°	76,8°	77,2°	77,5°	76,
Longitud del tubo superior (mm) (mm)	548	547	546	564	563	562	582	581	580	60,
Longitud del tubo de dirección (mm) (mm)	95			100			105			111
Ángulo del tubo de dirección	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,
Inclinación de la horquilla (mm)	44			44			44			44
Trail (mm) (mm)	134,2	131,3	128,3	134,1	131,3	128,3	134,1	131,3	128,3	13-
Distancia entre ejes (mm) (mm)	1159	1159	1158	1176	1176	1175	1202	1201	1201	12-
Longitud de la vaina (mm) (mm)	440	439	438	440	439	438	440	439	438	441
Caída del eje de pedalier (mm) (mm)	25	20	15	25	20	15	40	35	30	40
Stack (mm) (mm)	615	613	610	620	617	614	621	619	616	621
Reach (mm) (mm)	397	401	405	412	415	420	436	440	444	451
Altura del suelo al tubo (mm) (mm)	730	734	738	733	737	742	745	749	754	76
Ancho del manillar (mm) (mm)	760			760			760			781
Longitud de la potencia (mm) (mm)	40			50			50			50
Longitud de las bielas (mm) (mm)	165			170			170			171
Tamaño de ruedas	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F]

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.