



INTRIGUE X 1



SPECS

QUADRO	
TAMANHOS	XS, S, M, L
CORES	Gloss Black Diamond/Matte Black
QUADRO	ALUXX SL-grade aluminum front and rear triangles, 140mm Maestro Suspension, flip chip - Maestro 3, flip chip - headset, integrated down tube storage
FORQUILHA	Fox 36 Float Performance, 150mm, Grip damper, Boost 15x110 Kabolt X, tapered, 44mm offset
AMORTECEDORES	Fox Float Performance, 185x52.5, custom tuned for Liv
COMPONENTES	
GUIADOR	Giant Contact TR35, 20mm rise, alloy XS: 760mm, S: 760mm, M: 760mm, L: 780mm
PUNHOS	Liv Tactal Pro Single Lock-on XS/S: 120mm M/L: 130mm
AVANÇO	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
ESPIGÃO DE SELIM	Giant Contact Switch, adjustable dropper, remote XS: 140-170mm travel / 30.9 x 470mm S: 140-170mm travel / 30.9 x 470mm M: 170-200mm travel / 30.9 x 530mm L: 170-200mm travel / 30.9 x 530mm
SELIM	Liv Sylvia
PEDAIS	platform
TRANSMISSÃO	
MANETES	Shimano SLX M7100, 1x12
DESVIADOR DIANTEIRO	N/A
DESVIADOR TRASEIRO	Shimano SLX M7100, Shadow +
TRAVÕES	Shimano BR-MT520, hydraulic, Shimano RT-66 [F] 203mm, [R] 180mm
MANÍPULOS DOS TRAVÕES	Shimano BL-MT501
CASSETTE	Shimano SLX M7100, 10x51
CORRENTE	KMC X12
CONJUNTO PEDALEIRO	Shimano MT512-1, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
MOVIMENTO CENTRAL	Shimano, press fit

RODAS	
AROS	Giant TR alloy WheelSystem, 30mm rim inner width XS/S: [F] 29, [R] 27.5 M/L: [F] 29, [R] 29
CUBOS	alloy, sealed bearing
RAIOS	Sapim
PNEUS	Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	3M tailgate protector, tubeless prepared, integrated down tube storage bag, max tire size 2.5", max chainring size 34t

Preço: 4 199,00 €

GEOMETRIA

QUADRO	XS			S			M			L
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	
Comprimento do tubo do assento (mm)	370			390			420			450
Seat Post Insertion Depth (mm)	240			260			290			320
Ângulo do tubo do assento	76,2°	76,6°	76,9°	76,2°	76,6°	76,9°	76,8°	77,2°	77,5°	76,8°
Comprimento do tubo superior (mm)	548	547	546	564	563	562	582	581	580	603
Comprimento do tubo principal (mm)	95			100			105			110
Ângulo do tubo principal	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°
Garfo ancinho (mm)	44			44			44			44
Trilha (mm)	134,2	131,3	128,3	134,1	131,3	128,3	134,1	131,3	128,3	134
distância entre eixos (mm)	1159	1159	1158	1176	1176	1175	1202	1201	1201	1224
Comprimento Chain Stay (mm)	440	439	438	440	439	438	440	439	438	440
Suporte inferior (mm)	25	20	15	25	20	15	40	35	30	40
Pilha (mm)	615	613	610	620	617	614	621	619	616	626
Alcançar (mm)	397	401	405	412	415	420	436	440	444	456
Altura do standover (mm)	730	734	738	733	737	742	745	749	754	767
Largura do guidão (mm)	760			760			760			780
Comprimento da haste (mm)	40			50			50			50
Comprimento da Manivela (mm)	165			170			170			170
Tamanho da roda	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 25

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.