

INTRIGUE X 1



ŠPECIFIKÁCIE

RÁM	
VELKOSTI	XS, S, M, L
FARBY	Gloss Black Diamond/Matte Black
RÁM	ALUXX SL-grade aluminum front and rear triangles, 140mm Maestro Suspension, flip chip – Maestro 3, flip chip – headset, integrated down tube storage
VIDLICA	Fox 36 Float Performance, 150mm, Grip damper, Boost 15x110 Kabolt X, tapered, 44mm offset
TLMIČ	Fox Float Performance, 185x52.5, custom tuned for Liv
KOMPONENTY	
RIADIDLÁ	Giant Contact TR35, 20mm rise, alloy XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPY	Liv Tactal Pro Single Lock-on XS/S: 120mm M/L: 130mm
PREDSTAVEC	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
SEDLOVKA	Giant Contact Switch, adjustable dropper, remote XS: 140-170mm travel / 30.9 x 470mm S: 140-170mm travel / 30.9 x 470mm M: 170-200mm travel / 30.9 x 530mm L: 170-200mm travel / 30.9 x 530mm
SEDADLO	Liv Sylvia
PEDÁLE	platform
POHON	
RADENIE	Shimano SLX M7100, 1x12
PREŠMYKAČ	N/A
PREHADZOVAČKA	Shimano SLX M7100, Shadow +
BRZDY	Shimano BR-MT520, hydraulic, Shimano RT-66 [F] 203mm, [R] 180mm
BRZDOVÉ PÁKY	Shimano BL-MT501
KAZETA	Shimano SLX M7100, 10x51
REŤAZ	KMC X12
KLUKY	Shimano MT512-1, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
STREDOVÉ ZLOŽENIE	Shimano, press fit

KOLESÁ	
RÁFIKY	Giant TR alloy WheelSystem, 30mm rim inner width XS/S: [F] 29, [R] 27.5 M/L: [F] 29, [R] 29
NÁBOJE	alloy, sealed bearing
ŠPICE	Sapim
PNEUMATIKY	Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
DOPLNKY	3M tailgate protector, tubeless prepared, integrated down tube storage bag, max tire size 2.5", max chainring size 34t

Cena: 4 799 €

GEOMETRIA

RÁM	XS			S			M		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Dĺžka sedlovej trubky (mm)	370			390			420		
Hĺbka vloženia sedlovky (mm)	240			260			290		
Uhol sedlovej trubky	76,2°	76,6°	76,9°	76,2°	76,6°	76,9°	76,8°	77,2°	77,6°
Dĺžka hornej rámovej trubky (mm)	548	547	546	564	563	562	582	581	580
Dĺžka hlavovej trubky (mm)	95			100			105		
Uhol hlavovej trubky	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°
Offset vidlice (mm)	44			44			44		
Trail (mm)	134,2	131,3	128,3	134,1	131,3	128,3	134,1	131,3	128,3
Rázvor (mm)	1159	1159	1158	1176	1176	1175	1202	1201	1200
Dĺžka zadnej stavby (mm)	440	439	438	440	439	438	440	439	438
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	25	20	15	25	20	15	40	35	30
Stack - výška riadenia (mm)	615	613	610	620	617	614	621	619	616
Reach (mm)	397	401	405	412	415	420	436	440	444
Výška rámu od zeme (mm)	730	734	738	733	737	742	745	749	754
Šírka riaditok (mm)	760			760			760		
Dĺžka predstavca (mm)	40			50			50		
Dĺžka kľúk (mm)	165			170			170		
Rozmer kolies	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.