INTRIGUE X 2



SPECS

FRAME	
SIZES	XS, S, M
COLOURS	Morning Haze
FRAME	ALUXX SL-grade Aluminium front and rear triangles, 140mm Maestro suspension, flip chip 3 position, 12x148mm thru-axle, rear wheel, 27.5" [XS/S], 29" [M], integrated downtube storage, 55mm Chainline
FORK	Fox 36 Float Rhythm, 150mm, GRIP damper, 15x110mm Kabolt X thru-axle, 44mm offset
SHOCK	Fox Float Performance, 2 position, custom tuned for Liv
COMPONENTS	
HANDLEBAR	Giant Contact TR35, alloy, 20mm rise
GRIPS	Liv Tactal Pro Single lock-on
STEM	Giant Contact SL 35 XS: 40mm, S: 50mm, M: 50mm
SEATPOST	Giant Contact Switch AT dropper, adjustable travel, remote XS: 140-170mm travel / 30.9 x 470mm S: 140-170mm travel / 30.9 x 470mm M: 170-200mm travel / 30.9 x 530mm
SADDLE	Liv Sylvia
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano Deore, SL-M6200, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano Deore, M7200, Shadow
BRAKES	TRP EVO Comp, hydraulic, TRP [F] 203mm, [R] 180mm
BRAKE LEVERS	TRP EVO Comp
CASSETTE	Shimano Deore 6200, 10x51
CHAIN	KMC X12
CRANKSET	Praxis Cadet M24, 30T, Alloy Chainring, 55mm chainline XS:165mm, S:170mm, M:170mm
BOTTOM BRACKET	Praxis press fit

WHEELS	
RIMS	Giant TRA Hookless Tubeless ready Alloy, 30mm inner width 27.5" rear wheel [XS/S], 29" rear wheel [M]
HUBS	[F] Giant Boost Alloy Hub, 6 Bolt, Sealed Bearing, 28H [R] Giant Boost Alloy Hub, 6 Bolt, Sealed Bearing, HG, 28H
SPOKES	Sapim, 28, J-bend
TYRES	[F] Maxxis Assegai 29x2.5 WT, MaxxTerra, EXO, TR [R] Maxxis Minion DHR II 27.5x2.4 [XS/S], 29x2.4 [M], WT, MaxxTerra, EXO, TR tubeless
EXTRAS	Tubeless prepared, chain guide, 3M tailgate protector
LIMITS	
MAX TYRE CLEARANCE	2.5"
MAX CHAINRING SIZE	34t

Price: $4,499.00

GEOMETRY

FRAME	XS	S	M
	LOW | MID | HIGH	LOW | MID | HIGH	LOW | MID | HIGH
Seat Tube Length (mm)	370	390	420
Seat Post Insertion Depth (mm)	240	260	290
Seat Tube Angle	76.2° | 76.6° | 76.9°	76.2° | 76.6° | 76.9°	76.8° | 77.2° | 77.5°
Top Tube Length (mm)	548 | 547 | 546	564 | 563 | 562	582 | 581 | 580
Head Tube Length (mm)	95	100	105
Head Tube Angle	64.4° | 64.8° | 65.1°	64.4° | 64.8° | 65.1°	64.4° | 64.8° | 65.1°
Fork Rake (mm)	44	44	44
Trail (mm)	134.2 | 131.3 | 128.3	134.1 | 131.3 | 128.3	134.1 | 131.3 | 128.3
Wheelbase (mm)	1159 | 1159 | 1158	1176 | 1176 | 1175	1202 | 1201 | 1201
Chain Stay Length (mm)	440 | 439 | 438	440 | 439 | 438	440 | 439 | 438
Bottom Bracket Drop (mm)	25 | 20 | 15	25 | 20 | 15	40 | 35 | 30
Stack (mm)	615 | 613 | 610	620 | 617 | 614	621 | 619 | 616
Reach (mm)	397 | 401 | 405	412 | 415 | 420	436 | 440 | 444
Stand Over Height (mm)	730 | 734 | 738	733 | 737 | 742	745 | 749 | 754
Stem Length (mm)	40	50	50
Crank Length (mm)	165	170	170

*Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freighting and assembly costs.*