

# INTRIGUE X 2



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, L
<b>COLOURS</b>	Gloss Desert Dawn
<b>FRAME</b>	ALUXX SL-grade aluminium front and rear triangles, 140mm Maestro Suspension, flip chip - Maestro 3, flip chip - headset, integrated down tube storage
<b>FORK</b>	Fox 36 Float Rhythm, 150mm, Grip damper, Boost 15x110 Kabolt X, tapered, 44mm offset
<b>SHOCK</b>	Fox Float Performance, 185x52.5, custom tuned for Liv
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact TR35, 20mm rise, alloy
<b>GRIPS</b>	Liv Tactal Pro Single Lock-on
<b>STEM</b>	Giant Contact SL, 35mm
<b>SEATPOST</b>	Giant Contact Switch, adjustable dropper, remote XS&S: 140-170mm travel / 30.9 x 470mm M&L: 170-200mm travel / 30.9 x 530mm
<b>SADDLE</b>	Liv Sylvia
<b>PEDALS</b>	PEDALS NOT SUPPLIED
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano Deore, 1x12
<b>FRONT DERAILLEUR</b>	N/A
<b>REAR DERAILLEUR</b>	Shimano Deore, Shadow +
<b>BRAKES</b>	Shimano BR-MT420, hydraulic, Shimano RT-66 [F] 203mm, [R] 180mm
<b>BRAKE LEVERS</b>	Shimano BL-MT401
<b>CASSETTE</b>	Shimano Deore M6100, 10x51
<b>CHAIN</b>	KMC X12
<b>CRANKSET</b>	Praxis Cadet M24 Boost, 30t, 55mm chainline
<b>BOTTOM BRACKET</b>	Praxis, press fit

WHEELS	
<b>RIMS</b>	Giant AM, tubeless ready, sleeve-joint, 30mm inner width XS/S: [F] 29, [R] 27.5 M/L: [F] 29, [R] 29
<b>HUBS</b>	alloy, sealed bearing
<b>SPOKES</b>	Sapim
<b>TYRES</b>	Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
<b>EXTRAS</b>	3M tailgate protector, factory tubeless set up, integrated down tube storage bag
LIMITS	
<b>MAX TYRE CLEARANCE</b>	2.5"
<b>MAX CHAINRING SIZE</b>	34t

**Price: £3,299.00**

## GEOMETRY

FRAME	XS			S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	370			390			420			450		
Seat Post Insertion Depth (mm)	240			260			290			320		
Seat Tube Angle	76.2°	76.6°	76.9°	76.2°	76.6°	76.9°	76.8°	77.2°	77.5°	76.8°	77.2°	
Top Tube Length (mm)	548	547	546	564	563	562	582	581	580	603	602	601
Head Tube Length (mm)	95			100			105			110		
Head Tube Angle	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	
Fork Rake (mm)	44			44			44			44		
Trail (mm)	134.2	131.3	128.3	134.1	131.3	128.3	134.1	131.3	128.3	134	131.3	
Wheelbase (mm)	1159	1159	1158	1176	1176	1175	1202	1201	1201	1224	1224	
Chain Stay Length (mm)	440	439	438	440	439	438	440	439	438	440	439	438
Bottom Bracket Drop (mm)	25	20	15	25	20	15	40	35	30	40	35	30
Stack (mm)	615	613	610	620	617	614	621	619	616	626	623	620
Reach (mm)	397	401	405	412	415	420	436	440	444	456	459	463
Stand Over Height (mm)	730	734	738	733	737	742	745	749	754	767	771	775
Handlebar Width (mm)	760			760			760			780		
Stem Length (mm)	40			50			50			50		
Crank Length (mm)	165			170			170			170		
Wheel Size	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.