

INTRIGUE X 2



SPECS

FRAME	
SIZES	XS, S, M, L
COLOURS	Desert Dawn
FRAME	ALUXX SL-grade aluminum front and rear triangles, 140mm Maestro Suspension, flip chip - Maestro 3, flip chip - headset, integrated down tube storage
FORK	Fox 36 Float Rhythm, 150mm, GRIP damper, Boost 15x110 Kabolt X, tapered, 44mm offset
SHOCK	Fox Float Performance, 185x52.5, custom tuned for Liv
COMPONENTS	
HANDLEBAR	Giant Contact TR35, 20mm rise, alloy XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPS	Liv Tactal Pro single lock-on
STEM	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
SEATPOST	"Giant Contact Switch AT, adjustable dropper, remote XS/S: 140-170mm travel / 30.9 x 470mm M/L: 170-200mm travel / 30.9 x 530mm"
SADDLE	Liv Sylvia
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano Deore, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano Deore, Shadow +
BRAKES	Shimano BR-MT420, hydraulic, Shimano RT-66 [F] 203mm, [R] 180mm
BRAKE LEVERS	Shimano BL-MT401
CASSETTE	Shimano Deore M6100, 10x51
CHAIN	KMC X12
CRANKSET	Praxis Cadet M24 Boost, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	Praxis, press fit

WHEELS	
RIMS	Giant TRA 2 6061 alloy, sleevejoint, 30mm IW, 40mm OW, 21mm H, Wide Guard technology XS/S: [F] 29, [R] 27.5 M/L: [F] 29, [R] 29
HUBS	[F] Giant MTB alloy, 6-bolt, sealed [R] Giant MTB alloy, 6 bolt, 72t POE, 6-pawl, sealed
SPOKES	Sapim Race j-bend
TIRES	[F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless XS/S: [R] Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless M/L: [R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 34t max chainring size, integrated down tube storage bag

Suggested Retail Price (CDN): \$3,899.00

FRAME GEOMETRY

FRAME	XS			S			M			L	
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID
Seat Tube Length (mm)	370			390			420			450	
Seat Post Insertion Depth (mm)	240			260			290			320	
Seat Tube Angle	76.2°	76.6°	76.9°	76.2°	76.6°	76.9°	76.8°	77.2°	77.5°	76.8°	77.2°
Top Tube Length (mm)	548	547	546	564	563	562	582	581	580	603	602
Bottom Bracket Drop (mm)	95			100			105			110	
Head Tube Angle	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°
Fork Rake (mm)	44			44			44			44	
Trail (mm)	134.2	131.3	128.3	134.1	131.3	128.3	134.1	131.3	128.3	134	131.3
Wheelbase (mm)	1159	1159	1158	1176	1176	1175	1202	1201	1201	1224	1224
Chain Stay Length (mm)	440	439	438	440	439	438	440	439	438	440	439
Bottom Bracket Drop (mm)	25	20	15	25	20	15	40	35	30	40	35
Stack (mm)	615	613	610	620	617	614	621	619	616	626	623
Reach (mm)	397	401	405	412	415	420	436	440	444	456	459
Stand Over Height (mm)	730	734	738	733	737	742	745	749	754	767	771
Handlebar Width (mm)	760			760			760			780	
Stem Length (mm)	40			50			50			50	
Crank Length (mm)	165			170			170			170	
Wheel Size	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]	

All prices and specifications are subject to change without notice.