



ŠPECIFIKÁCIE

RÁM	
VELKOSTI	XS, S, M, L
FARBY	Desert Dawn
RÁM	ALUXX SL-grade aluminum front and rear triangles, 140mm Maestro Suspension, flip chip – Maestro 3, flip chip – headset, integrated down tube storage
VIDLICA	Fox 36 Float Rhythm, 150mm, Grip damper, Boost 15x110 Kabolt X, tapered, 44mm offset
TLMIČ	Fox Float Performance, 185x52.5, custom tuned for Liv
KOMPONENTY	
RIADIDLÁ	Giant Contact TR35, 20mm rise, alloy XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPY	Liv Tactal Pro Single Lock-on XS/S: 120mm M/L: 130mm
PREDSTAVEC	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
SEDOVKA	Giant Contact Switch, adjustable dropper, remote XS: 140-170mm travel / 30.9 x 470mm S: 140-170mm travel / 30.9 x 470mm M: 170-200mm travel / 30.9 x 530mm L: 170-200mm travel / 30.9 x 530mm
SEDADLO	Liv Sylvia
PEDÁLE	platform
POHON	
RADENIE	Shimano Deore, 1x12
PREŠMYKAČ	N/A
PREHADZOVAČKA	Shimano Deore, Shadow +
BRZDY	Shimano BR-MT420, hydraulic, Shimano RT-66 [F] 203mm, [R] 180mm
BRZDOVÉ PÁKY	Shimano BL-MT401
KAZETA	Shimano Deore M6100, 10x51
REŤAZ	KMC X12
KLUKY	Praxis Cadet M24 Boost, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
STREDOVÉ ZLOŽENIE	Praxis, press fit

KOLESÁ	
RÁFIKY	Giant AM, tubeless ready, sleeve-joint, 30mm inner width XS/S: [F] 29, [R] 27.5 M/L: [F] 29, [R] 29
NÁBOJE	alloy, sealed bearing
ŠPICE	Sapim
PNEUMATIKY	Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
DOPLNKY	3M tailgate protector, tubeless prepared, integrated down tube storage bag, max tire size 2.5", max chainring size 34t

Cena: 3 499 €

GEOMETRIA

RÁM	XS			S			M		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Dĺžka sedlovej trubky (mm)	370			390			420		
Hĺbka vloženia sedlovky (mm)	240			260			290		
Uhol sedlovej trubky	76,2° 76,6° 76,9°			76,2° 76,6° 76,9°			76,8° 77,2° 77,6°		
Dĺžka hornej rámovej trubky (mm)	548 547 546			564 563 562			582 581 580		
Dĺžka hlavovej trubky (mm)	95			100			105		
Uhol hlavovej trubky	64,4° 64,8° 65,1°			64,4° 64,8° 65,1°			64,4° 64,8° 65,1°		
Offset vidlice (mm)	44			44			44		
Trail (mm)	134,2 131,3 128,3			134,1 131,3 128,3			134,1 131,3 128,3		
Rázvor (mm)	1159 1159 1158			1176 1176 1175			1202 1201 1200		
Dĺžka zadnej stavby (mm)	440 439 438			440 439 438			440 439 438		
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	25 20 15			25 20 15			40 35 30		
Stack - výška riadenia (mm)	615 613 610			620 617 614			621 619 616		
Reach (mm)	397 401 405			412 415 420			436 440 444		
Výška rámu od zeme (mm)	730 734 738			733 737 742			745 749 754		
Šírka riaditok (mm)	760			760			760		
Dĺžka predstavca (mm)	40			50			50		
Dĺžka kľúk (mm)	165			170			170		
Rozmer kolies	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.