INTRIGUE X ADVANCED 0



СПЕЦИФИКАЦИИ

РАМКА	
РАЗМЕР	XS, S, M, L
ЦВЯТ	Mulberry Glitter/Chrome
РАМКА	Advanced-grade composite front and rear triangles, 140mm Maestro Suspension, flip chip – Maestro 3, flip chip – headset, integrated down tube storage
ВИЛКА	Fox 36 Factory, 150mm, Grip 2 damper, Boost 15x110 Kabolt X, tapered, 44mm offset
ЗАДЕН АМОРТИСЬОР	Fox Float X Factory, 185x52.5, custom tuned for Liv
КОМПОНЕНТИ	
КОРМИЛО	Giant Contact SLR TR35, integrated, 20mm rise, composite XS: 800mm, S: 800mm, M: 800mm, L: 800mm
ГРИПОВЕ	Liv Tactal Pro Single Lock-on XS/S: 120mm M/L: 130mm
ЛАПА	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
КОЛЧЕ ЗА СЕДАЛКА	Giant Contact Switch, adjustable dropper, remote XS: 140-170mm travel / 30.9 x 470mm S: 140-170mm travel / 30.9 x 470mm M: 170-200mm travel / 30.9 x 530mm L: 170-200mm travel / 30.9 x 530mm
СЕДАЛКА	Liv Sylvia
ПЕДАЛИ	platform
DRIVETRAIN	
КОМАНДИ	SRAM AXS, 1x12
ПРЕДЕН ДЕРАЙЛЬОР	N/A
ЗАДЕН ДЕРАЙЛЬОР	SRAM XO Eagle AXS
СПИРАЧКИ	Shimano XT M8120, hydraulic, Shimano RT-66 rotors [F] 203mm, [R] 180mm
РЪКОХВАТКИ ЗА СПИРАЧКИ	Shimano XT BL-8100
КАСЕТА	SRAM XO, 10x52
ВЕРИГА	SRAM XO Eagle
КУРБЕЛ	SRAM XO, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
СРЕДНА КАСЕТА	SRAM DUB, press fit

КАПЛИ	
ШИНИ	Giant TRX carbon WheelSystem, 30mm rim inner width XS/S: [F] 29, [R] 27.5 M/L: [F] 29, [R] 29
ГЛАВИНИ	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
СПИЦИ	Sapim
ГУМИ	Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
ЕКСТРИ	3M tailgate protector, tubeless prepared, integrated down tube storage bag, max tire size 2.5", max chainring size 34t

ГЕОМЕТРИЯ

РАМКА	XS	S	M	L
	LOW | MID | HIGH	LOW | MID | HIGH	LOW | MID | HIGH	LOW | MID |
Seat Tube Length (mm)	370	390	420	450
Seat Post Insertion Depth (mm)	240	260	290	320
Seat Tube Angle	76,2° | 76,6° | 76,9°	76,2° | 76,6° | 76,9°	76,8° | 77,2° | 77,5°	76,8° | 77,2°
Top Tube Length (mm)	548 | 547 | 546	564 | 563 | 562	582 | 581 | 580	603 | 602 | 6
Head Tube Length (mm)	95	100	105	110
Head Tube Angle	64,4° | 64,8° | 65,1°	64,4° | 64,8° | 65,1°	64,4° | 64,8° | 65,1°	64,4° | 64,8°
Fork Rake (mm)	44	44	44	44
Trail (mm)	134,2 | 131,3 | 128,3	134,1 | 131,3 | 128,3	134,1 | 131,3 | 128,3	134 | 131,3 |
Wheelbase (mm)	1159 | 1159 | 1158	1176 | 1176 | 1175	1202 | 1201 | 1201	1224 | 1224 |
Chain Stay Length (mm)	440 | 439 | 438	440 | 439 | 438	440 | 439 | 438	440 | 439 | 4
Bottom Bracket Drop (mm)	25 | 20 | 15	25 | 20 | 15	40 | 35 | 30	40 | 35 | 30
Stack (mm)	615 | 613 | 610	620 | 617 | 614	621 | 619 | 616	626 | 623 | 6
Обсег (mm)	397 | 401 | 405	412 | 415 | 420	436 | 440 | 444	456 | 459 | 4
Stand Over Height (mm)	730 | 734 | 738	733 | 737 | 742	745 | 749 | 754	767 | 771 | 7
Ширина на Кормило (mm)	760	760	760	780
Дължина на Лапа (mm)	40	50	50	50
Дължина на Курбел (mm)	165	170	170	170
Размер на Каплите	[F] 29" [R	[F] 29" [R	[F] 29" [R	[F] 29" [R

All specifications listed are subject to change without notice.