# INTRIGUE X ADVANCED 0




## SPECIFIKACIJE

| OKVIR | |
|---|---|
| **VELIČINE** | XS, S, M, L |
| **BOJE** | Mulberry Glitter/Chrome |
| **OKVIR** | Advanced-grade composite front and rear triangles, 140mm Maestro Suspension, flip chip – Maestro 3, flip chip – headset, integrated down tube storage |
| **VILICA** | Fox 36 Factory, 150mm, Grip 2 damper, Boost 15x110 Kabolt X, tapered, 44mm offset |
| **AMORTIZER** | Fox Float X Factory, 185x52.5, custom tuned for Liv |
| **KOMPONENTE** | |
| **VOLAN** | Giant Contact SLR TR35, integrated, 20mm rise, composite XS: 800mm, S: 800mm, M: 800mm, L: 800mm |
| **GRIPS** | Liv Tactal Pro Single Lock-on XS/S: 120mm M/L: 130mm |
| **LULA VOLANA** | Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm |
| **CIJEV SJEDALA** | Giant Contact Switch, adjustable dropper, remote XS: 140-170mm travel / 30.9 x 470mm S: 140-170mm travel / 30.9 x 470mm M: 170-200mm travel / 30.9 x 530mm L: 170-200mm travel / 30.9 x 530mm |
| **SJEDALO** | Liv Sylvia |
| **PEDALE** | platform |
| **POGON** | |
| **RUČICE MJENJAČA** | SRAM AXS, 1x12 |
| **PREDNJI MJENJAČ** | N/A |
| **STRAŽNJI MJENJAČ** | SRAM XO Eagle AXS |
| **KOČNICE** | Shimano XT M8120, hydraulic, Shimano RT-66 rotors [F] 203mm, [R] 180mm |
| **RUČICE KOČNICA** | Shimano XT BL-8100 |
| **KAZETA** | SRAM XO, 10x52 |
| **LANAC** | SRAM XO Eagle |
| **POGON** | SRAM XO, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm |
| **OSOVINA POGONA (BB)** | SRAM DUB, press fit |

| KOTAČI | |
|---|---|
| **OBRUČI** | Giant TRX carbon WheelSystem, 30mm rim inner width XS/S: [F] 29, [R] 27.5 M/L: [F] 29, [R] 29 |
| **NABE** | [F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt |
| **ŽBICE** | Sapim |
| **GUME** | Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless |
| **DODACI** | 3M tailgate protector, tubeless prepared, integrated down tube storage bag, max tire size 2.5", max chainring size 34t |

## GEOMETRIJA

| OKVIR | XS | S |
|---|---|---|
| | LOW \| MID \| HIGH | LOW \| MID \| HIGH |
| Dužina cijevi sjedala (mm) | 370 | 390 |
| Seat Post Insertion Depth (mm) | 240 | 260 |
| Kut cijevi sjedala | 76,2° \| 76,6° \| 76,9° | 76,2° \| 76,6° \| 76,9° |
| Dužina gornje cijevi (mm) | 548 \| 547 \| 546 | 564 \| 563 \| 562 |
| Dužina prednje cijevi (mm) | 95 | 100 |
| Kut vilice | 64,4° \| 64,8° \| 65,1° | 64,4° \| 64,8° \| 65,1° |
| Zakrivljenost vilice (offset) (mm) | 44 | 44 |
| Staza (mm) | 134,2 \| 131,3 \| 128,3 | 134,1 \| 131,3 \| 128,3 |
| Međuosovinski razmak kotača (mm) | 1159 \| 1159 \| 1158 | 1176 \| 1176 \| 1175 |
| Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm) | 440 \| 439 \| 438 | 440 \| 439 \| 438 |
| Položaj osovine pogona (mm) | 25 \| 20 \| 15 | 25 \| 20 \| 15 |
| Vertikalna dužina od osovine pogona do glave okvira (stack) (mm) | 615 \| 613 \| 610 | 620 \| 617 \| 614 |
| Horizontalna dužina od osovine pogona do glave okvira (reach) (mm) | 397 \| 401 \| 405 | 412 \| 415 \| 420 |
| Prekoračna visina (mm) | 730 \| 734 \| 738 | 733 \| 737 \| 742 |
| Širina volana (mm) | 760 | 760 |
| Dužina lule volana (mm) | 40 | 50 |
| Dužina poluge pedale (mm) | 165 | 170 |
| Veličina kotača | [F] 29" [R | [F] 29" [R |

*Sve navedene specifikacije podložne su promjeni bez prethodne najave.*