INTRIGUE X ADVANCED 0



SPECS

RAMME	
STØRRELSE	XS, S, M, L
FARGE	Mulberry Glitter/Chrome
RAMME	Advanced-grade composite front and rear triangles, 140mm Maestro Suspension, flip chip – Maestro 3, flip chip – headset, integrated down tube storage
GAFFEL	Fox 36 Factory, 150mm, Grip 2 damper, Boost 15x110 Kabolt X, tapered, 44mm offset
DEMPER	Fox Float X Factory, 185x52.5, custom tuned for Liv
KOMPONENTER	
STYRE	Giant Contact SLR TR35, integrated, 20mm rise, composite XS: 800mm, S: 800mm, M: 800mm, L: 800mm
GRIPS	Liv Tactal Pro Single Lock-on XS/S: 120mm M/L: 130mm
STYRSTEM	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
SETEPINNE	Giant Contact Switch, adjustable dropper, remote XS: 140-170mm travel / 30.9 x 470mm S: 140-170mm travel / 30.9 x 470mm M: 170-200mm travel / 30.9 x 530mm L: 170-200mm travel / 30.9 x 530mm
SADEL	Liv Sylvia
PEDALER	platform
DRIVVERK	
GIRHENDLER	SRAM AXS, 1x12
FRONTGIR	N/A
BAKGIR	SRAM XO Eagle AXS
BREMSER	Shimano XT M8120, hydraulic, Shimano RT-66 rotors [F] 203mm, [R] 180mm
BREMSEHENDLER	Shimano XT BL-8100
KASSETT	SRAM XO, 10x52
KJEDE	SRAM XO Eagle
KRANK	SRAM XO, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	SRAM DUB, press fit

HJUL	
FELG	Giant TRX carbon WheelSystem, 30mm rim inner width XS/S: [F] 29, [R] 27.5 M/L: [F] 29, [R] 29
NAV	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
EIKE	Sapim
DEKK	Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	3M tailgate protector, tubeless prepared, integrated down tube storage bag, max tire size 2.5", max chainring size 34t

GEOMETRI

RAMME	XS	S	M	L
	LOW | MID | HIGH	LOW | MID | HIGH	LOW | MID | HIGH	LOW | MID |
Seat Tube Length (mm)	370	390	420	450
Seat Post Insertion Depth (mm)	240	260	290	320
Seat Tube Angle	76,2° | 76,6° | 76,9°	76,2° | 76,6° | 76,9°	76,8° | 77,2° | 77,5°	76,8° | 77,2°
Top Tube Length (mm)	548 | 547 | 546	564 | 563 | 562	582 | 581 | 580	603 | 602 | 6
Head Tube Length (mm)	95	100	105	110
Head Tube Angle	64,4° | 64,8° | 65,1°	64,4° | 64,8° | 65,1°	64,4° | 64,8° | 65,1°	64,4° | 64,8°
Fork Rake (mm)	44	44	44	44
Trail (mm)	134,2 | 131,3 | 128,3	134,1 | 131,3 | 128,3	134,1 | 131,3 | 128,3	134 | 131,3 |
Wheelbase (mm)	1159 | 1159 | 1158	1176 | 1176 | 1175	1202 | 1201 | 1201	1224 | 1224 |
Chain Stay Length (mm)	440 | 439 | 438	440 | 439 | 438	440 | 439 | 438	440 | 439 | 4
Bottom Bracket Drop (mm)	25 | 20 | 15	25 | 20 | 15	40 | 35 | 30	40 | 35 | 30
Stack (mm)	615 | 613 | 610	620 | 617 | 614	621 | 619 | 616	626 | 623 | 6
Reach (mm)	397 | 401 | 405	412 | 415 | 420	436 | 440 | 444	456 | 459 | 4
Stand Over Height (mm)	730 | 734 | 738	733 | 737 | 742	745 | 749 | 754	767 | 771 | 7
Handlebar Width (mm)	760	760	760	780
Stem Length (mm)	40	50	50	50
Crank Length (mm)	165	170	170	170
Wheel Size	[F] 29" [R	[F] 29" [R	[F] 29" [R	[F] 29" [R

Alle spesifikasjonene kan endres uten varsel.