

INTRIGUE X ADVANCED 1



SPECS

FRAME	
SIZES	XS, S, M, L
COLOURS	Gloss Raw Carbon/Chrome
FRAME	Advanced-grade composite front and rear triangles, 140mm Maestro Suspension, flip chip - Maestro 3, flip chip - headset, integrated down tube storage
FORK	Fox 36 Performance Elite, 150mm, Grip 2 damper, Boost 15x110 Kabolt X, tapered, 44mm offset
SHOCK	Fox Float X Performance Elite, 185x52.5, custom tuned for Liv
COMPONENTS	
HANDLEBAR	Giant Contact SLR TR35, 20mm rise, composite
GRIPS	Liv Tactal Pro Single Lock-on
STEM	Giant Contact SL, 35mm
SEATPOST	Giant Contact Switch, adjustable dropper, remote XS&S: 140-170mm travel / 30.9 x 470mm M&L: 170-200mm travel / 30.9 x 530mm
SADDLE	Liv Sylvia
PEDALS	PEDALS NOT SUPPLIED
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM GX Eagle Transmission AXS
BRAKES	Shimano XT M8120, hydraulic, Shimano RT-66 rotors [F] 203mm, [R] 180mm
BRAKE LEVERS	Shimano XT BL-8100
CASSETTE	SRAM GX CS 1275 T-Type, 10x52
CHAIN	SRAM GX T-Type
CRANKSET	SRAM GX T-Type, 30t, 55mm chainline
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant TRX 27.5"/29" hookless carbon wheelsystem 30mm rim inner width 40mm outer width 72t, POE, 28 SP spokes, DBL technology XD driver body 27.5"/R/29" F for frame sizes XS/S 29" F&R for frame sizes for M/L
HUBS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
SPOKES	Sapim
TYRES	Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	3M tailgate protector, factory tubeless set up, integrated down tube storage bag,
LIMITS	
MAX TYRE CLEARANCE	2.5"
MAX CHAINRING SIZE	34t

Price: £5,999.00

GEOMETRY

FRAME	XS			S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	370			390			420			450		
Seat Post Insertion Depth (mm)	240			260			290			320		
Seat Tube Angle	76.2°	76.6°	76.9°	76.2°	76.6°	76.9°	76.8°	77.2°	77.5°	76.8°	77.2°	
Top Tube Length (mm)	548	547	546	564	563	562	582	581	580	603	602	601
Head Tube Length (mm)	95			100			105			110		
Head Tube Angle	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	
Fork Rake (mm)	44			44			44			44		
Trail (mm)	134.2	131.3	128.3	134.1	131.3	128.3	134.1	131.3	128.3	134	131.3	
Wheelbase (mm)	1159	1159	1158	1176	1176	1175	1202	1201	1201	1224	1224	
Chain Stay Length (mm)	440	439	438	440	439	438	440	439	438	440	439	438
Bottom Bracket Drop (mm)	25	20	15	25	20	15	40	35	30	40	35	30
Stack (mm)	615	613	610	620	617	614	621	619	616	626	623	619
Reach (mm)	397	401	405	412	415	420	436	440	444	456	459	463
Stand Over Height (mm)	730	734	738	733	737	742	745	749	754	767	771	775
Handlebar Width (mm)	760			760			760			780		
Stem Length (mm)	40			50			50			50		
Crank Length (mm)	165			170			170			170		
Wheel Size	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.