

INTRIGUE X ADVANCED 1



SPECS

RAMME	
STØRRELSE	XS, S, M, L
FARGE	Raw Carbon/Chrome
RAMME	Advanced-grade composite front and rear triangles, 140mm Maestro Suspension, flip chip – Maestro 3, flip chip – headset, integrated down tube storage
GAFFEL	Fox 36 Performance Elite, 150mm, Grip 2 damper, Boost 15x110 Kabolt X, tapered, 44mm offset
DEMPER	Fox Float X Performance Elite, 185x52.5, custom tuned for Liv
KOMPONENTER	
STYRE	Giant Contact SLR TR35, 20mm rise, composite XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPS	Liv Tactal Pro Single Lock-on XS/S: 120mm M/L: 130mm
STYRSTEM	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
SETEPINNE	Giant Contact Switch, adjustable dropper, remote XS: 140-170mm travel / 30.9 x 470mm S: 140-170mm travel / 30.9 x 470mm M: 170-200mm travel / 30.9 x 530mm L: 170-200mm travel / 30.9 x 530mm
SADEL	Liv Sylvia
PEDALER	platform
DRIVVERK	
GIRHENDLER	SRAM AXS Pod, 1x12
FRONTGIR	N/A
BAKGIR	SRAM GX Eagle, T-Type AXS
BREMSER	Shimano XT M8120, hydraulic, Shimano RT-66 rotors [F] 203mm, [R] 180mm
BREMSEHENDLER	Shimano XT BL-8100
KASSETT	SRAM GX CS 1275 T-Type, 10x52
KJEDE	SRAM GX T-Type
KRANK	SRAM GX T-Type, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	SRAM DUB, press fit

HJUL	
FELG	Giant TRX carbon WheelSystem, 30mm rim inner width XS/S: [F] 29, [R] 27.5 M/L: [F] 29, [R] 29
NAV	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
EIKE	Sapim
DEKK	Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	3M tailgate protector, tubeless prepared, integrated down tube storage bag, max tire size 2.5", max chaining size 34t

GEOMETRI

RAMME	XS			S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	370			390			420			450		
Seat Post Insertion Depth (mm)	240			260			290			320		
Seat Tube Angle	76,2°	76,6°	76,9°	76,2°	76,6°	76,9°	76,8°	77,2°	77,5°	76,8°	77,2°	
Top Tube Length (mm)	548	547	546	564	563	562	582	581	580	603	602	601
Head Tube Length (mm)	95			100			105			110		
Head Tube Angle	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°	64,8°	
Fork Rake (mm)	44			44			44			44		
Trail (mm)	134,2	131,3	128,3	134,1	131,3	128,3	134,1	131,3	128,3	134	131,3	
Wheelbase (mm)	1159	1159	1158	1176	1176	1175	1202	1201	1201	1224	1224	
Chain Stay Length (mm)	440	439	438	440	439	438	440	439	438	440	439	438
Bottom Bracket Drop (mm)	25	20	15	25	20	15	40	35	30	40	35	30
Stack (mm)	615	613	610	620	617	614	621	619	616	626	623	620
Reach (mm)	397	401	405	412	415	420	436	440	444	456	459	463
Stand Over Height (mm)	730	734	738	733	737	742	745	749	754	767	771	775
Handlebar Width (mm)	760			760			760			780		
Stem Length (mm)	40			50			50			50		
Crank Length (mm)	165			170			170			170		
Wheel Size	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

Alle spesifikasjonene kan endres uten varsel.