

INTRIGUE X ADVANCED 1



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, L
BARVE	Raw Carbon/Chrome
OKVIR	Advanced-grade composite front and rear triangles, 140mm Maestro Suspension, flip chip – Maestro 3, flip chip – headset, integrated down tube storage
VILICE	Fox 36 Performance Elite, 150mm, Grip 2 damper, Boost 15x110 Kabolt X, tapered, 44mm offset
AMORTIZER	Fox Float X Performance Elite, 185x52.5, custom tuned for Liv
KOMPONENTE	
KRMILO	Giant Contact SLR TR35, 20mm rise, composite XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPS	Liv Tactal Pro Single Lock-on XS/S: 120mm M/L: 130mm
OPORA KRMILA	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
OPORA SEDEŽA	Giant Contact Switch, adjustable dropper, remote XS: 140-170mm travel / 30.9 x 470mm S: 140-170mm travel / 30.9 x 470mm M: 170-200mm travel / 30.9 x 530mm L: 170-200mm travel / 30.9 x 530mm
SEDEŽ	Liv Sylvia
PEDALA	platform
POGON	
PRESTAVNE ROČICE	SRAM AXS Pod, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM GX Eagle, T-Type AXS
ZAVORE	Shimano XT M8120, hydraulic, Shimano RT-66 rotors [F] 203mm, [R] 180mm
ZAVORNE ROČICE	Shimano XT BL-8100
VERIŽNIK	SRAM GX CS 1275 T-Type, 10x52
VERIGA	SRAM GX T-Type
GONILKE Z VERIŽNIKI	SRAM GX T-Type, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant TRX carbon WheelSystem, 30mm rim inner width XS/S: [F] 29, [R] 27.5 M/L: [F] 29, [R] 29
PESTA	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
NAPERRE	Sapim
PLAŠČI	Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
DODATKI	3M tailgate protector, tubeless prepared, integrated down tube storage bag, max tire size 2.5", max chainring size 34t

GEOMETRIJA

OKVIR	XS			S			M		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Dolžina sedežne cevi (mm)	370			390			420		
Seat Post Insertion Depth (mm)	240			260			290		
Kot sedežne cevi	76,2° 76,6° 76,9°			76,2° 76,6° 76,9°			76,8° 77,2° 77,5°		
Top Tube Length (mm)	548 547 546			564 563 562			582 581 580		
Višina glave okvirja (mm)	95			100			105		
Krmilni kot	64,4° 64,8° 65,1°			64,4° 64,8° 65,1°			64,4° 64,8° 65,1°		
Zamik vpetja osi (mm)	44			44			44		
Trail (mm)	134,2 131,3 128,3			134,1 131,3 128,3			134,1 131,3 128,3		
Medosna razdalja (mm)	1159 1159 1158			1176 1176 1175			1202 1201 1201		
Dolžina cevi ob verigi (mm)	440 439 438			440 439 438			440 439 438		
Bottom Bracket Drop (mm)	25 20 15			25 20 15			40 35 30		
Oddaljenost zgornje cevi od gonilne osi (mm)	615 613 610			620 617 614			621 619 616		
Doseg (mm)	397 401 405			412 415 420			436 440 444		
Višina zgornje cevi (mm)	730 734 738			733 737 742			745 749 754		
Širina krmila (mm)	760			760			760		
Dolžina opore krmila (mm)	40			50			50		
Dolžina gonilke (mm)	165			170			170		
Velikost obročnikov	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

Vse navedene specifikacije se lahko spremenijo brez obvestila.