

INTRIGUE X ADVANCED 2



SPECS

FRAME	
SIZES	XS, S, M, L
COLOURS	Shoreline
FRAME	Advanced-grade composite front and rear triangles, 140mm Maestro Suspension, 12x148mm thru-axle, flip chip – Maestro 3, flip chip – headset, integrated down tube storage, under-top tube storage mounts
FORK	Fox 36 Float Rhythm, 150mm, GRIP damper, Boost 15x110 Kabolt X, tapered, 44mm offset
SHOCK	Fox Float Performance, 185x52.5, custom tuned for Liv, recommended sag 30%
COMPONENTS	
HANDLEBAR	Giant Contact TR35, 20mm rise, alloy XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPS	Liv Tactal Pro Single Lock-on XS/S: 120mm M/L: 130mm
STEM	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
SEATPOST	Giant Contact Switch AT dropper, remote XS: 140-170mm travel / 30.9 x 470mm S: 140-170mm travel / 30.9 x 470mm M: 170-200mm travel / 30.9 x 530mm L: 170-200mm travel / 30.9 x 530mm
SADDLE	Liv Sylvia
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano Deore, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano Deore, Shadow +
BRAKES	Shimano BR-MT420, hydraulic, Shimano RT-66 [F] 203mm, [R] 180mm
BRAKE LEVERS	Shimano BL-MT401
CASSETTE	Shimano Deore M6100, 10x51
CHAIN	KMC X12
CRANKSET	Praxis Cadet HD M24 Boost, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant TRX WheelSystem, carbon, 30mm rim inner width, 40mm outer width, 22mm height, Wide Guard Technology XS/S: [F] 29, [R] 27.5 M/L: [F] 29, [R] 29
HUBS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 72 POE (Points of Engagement), 6-bolt, MicroSpline driver body
SPOKES	Sapim, 28, straight pull, DBL Technology
TIRES	Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	3M tailgate protector, tubeless prepared, integrated down tube storage bag, max tire size 2.5", max chainring size 34t

Suggested Retail Price (CDN): \$5,699.00

FRAME GEOMETRY

FRAME	XS			S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	370			390			420			450		
Seat Post Insertion Depth (mm)	240			260			290			320		
Seat Tube Angle	76.2°	76.6°	76.9°	76.2°	76.6°	76.9°	76.8°	77.2°	77.5°	76.8°	77.2°	
Top Tube Length (mm)	548	547	546	564	563	562	582	581	580	603	602	601
Head Tube Length (mm)	95			100			105			110		
Head Tube Angle	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	
Fork Rake (mm)	44			44			44			44		
Trail (mm)	134.2	131.3	128.3	134.1	131.3	128.3	134.1	131.3	128.3	134	131.3	
Wheelbase (mm)	1159	1159	1158	1176	1176	1175	1202	1201	1201	1224	1224	
Chain Stay Length (mm)	440	439	438	440	439	438	440	439	438	440	439	438
Bottom Bracket Drop (mm)	25	20	15	25	20	15	40	35	30	40	35	30
Stack (mm)	615	613	610	620	617	614	621	619	616	626	623	620
Reach (mm)	397	401	405	412	415	420	436	440	444	456	459	463
Stand Over Height (mm)	730	734	738	733	737	742	745	749	754	767	771	775
Handlebar Width (mm)	760			760			760			780		
Stem Length (mm)	40			50			50			50		
Crank Length (mm)	165			170			170			170		
Wheel Size	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

All prices and specifications are subject to change without notice.