

# INTRIGUE X ADVANCED 2



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, L
<b>COLOURS</b>	Shoreline
<b>FRAME</b>	Advanced-grade composite front and rear triangles, 140mm Maestro Suspension, 12x148mm thru-axle, flip chip - Maestro 3, flip chip - headset, integrated down tube storage, under-top tube storage mounts
<b>FORK</b>	Fox 36 Float Rhythm, 150mm, GRIP damper, Boost 15x110 Kabolt X, tapered, 44mm offset
<b>SHOCK</b>	Fox Float Performance, 185x52.5, custom tuned for Liv, recommended sag 30%
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact TR35, 20mm rise, alloy XS: 760mm, S: 760mm, M: 760mm, L: 780mm
<b>GRIPS</b>	Liv Tactal Pro Single Lock-on XS/S: 120mm M/L: 130mm
<b>STEM</b>	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
<b>SEATPOST</b>	Giant Contact Switch AT dropper, remote XS: 140-170mm travel / 30.9 x 470mm S: 140-170mm travel / 30.9 x 470mm M: 170-200mm travel / 30.9 x 530mm L: 170-200mm travel / 30.9 x 530mm
<b>SADDLE</b>	Liv Sylvia
<b>PEDALS</b>	N/A
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano Deore, 1x12
<b>FRONT DERAILLEUR</b>	N/A
<b>REAR DERAILLEUR</b>	Shimano Deore, Shadow +
<b>BRAKES</b>	Shimano BR-MT420, hydraulic, Shimano RT-66 [F] 203mm, [R] 180mm
<b>BRAKE LEVERS</b>	Shimano BL-MT401
<b>CASSETTE</b>	Shimano Deore M6100, 10x51
<b>CHAIN</b>	KMC X12
<b>CRANKSET</b>	Praxis Cadet HD M24 Boost, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
<b>BOTTOM BRACKET</b>	Shimano, press fit

WHEELS	
<b>RIMS</b>	Giant TRX WheelSystem, carbon, 30mm rim inner width, 40mm outer width, 22mm height, Wide Guard Technology XS/S: [F] 29, [R] 27.5 M/L: [F] 29, [R] 29
<b>HUBS</b>	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 72 POE (Points of Engagement), 6-bolt, MicroSpline driver body
<b>SPOKES</b>	Sapim, 28, straight pull, DBL Technology
<b>TIRES</b>	Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
<b>EXTRAS</b>	3M tailgate protector, tubeless prepared, integrated down tube storage bag, max tire size 2.5", max chainring size 34t

**Suggested Retail Price (CDN): \$5,699.00**

## FRAME GEOMETRY

FRAME	XS			S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	370			390			420			450		
Seat Post Insertion Depth (mm)	240			260			290			320		
Seat Tube Angle	76.2°	76.6°	76.9°	76.2°	76.6°	76.9°	76.8°	77.2°	77.5°	76.8°	77.2°	
Top Tube Length (mm)	548	547	546	564	563	562	582	581	580	603	602	601
Head Tube Length (mm)	95			100			105			110		
Head Tube Angle	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°
Fork Rake (mm)	44			44			44			44		
Trail (mm)	134.2	131.3	128.3	134.1	131.3	128.3	134.1	131.3	128.3	134	131.3	
Wheelbase (mm)	1159	1159	1158	1176	1176	1175	1202	1201	1201	1224	1224	
Chain Stay Length (mm)	440	439	438	440	439	438	440	439	438	440	439	438
Bottom Bracket Drop (mm)	25	20	15	25	20	15	40	35	30	40	35	30
Stack (mm)	615	613	610	620	617	614	621	619	616	626	623	619
Reach (mm)	397	401	405	412	415	420	436	440	444	456	459	463
Stand Over Height (mm)	730	734	738	733	737	742	745	749	754	767	771	775
Handlebar Width (mm)	760			760			760			780		
Stem Length (mm)	40			50			50			50		
Crank Length (mm)	165			170			170			170		
Wheel Size	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

All prices and specifications are subject to change without notice.