

INTRIGUE X ADVANCED E+ ELITE 1



SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro2 85Nm, powered by Yamaha
STEUEREINHEIT	RideControl Ergo 3, RideControl GO integrated in T/T
DISPLAY	ANT+ Wireless display compatible
AKKU	EnergyPak Smart Compact 400, EnergyPak Plus range extender compatible
RAHMEN	
GRÖSSEN	XS, S, M, L
FARBE	Airglow
RAHMEN	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension systemMX (front 29", rear 27.5")
GABEL	Fox 36 Performance Elite Live Valve, 150mm travel, 44mm offset, Grip2 damper, Boost 110x15QR, electronic adaptive suspension, e-bike integrated, e-bike integrated
DÄMPFER	Fox Float X Live Valve, 185x52.5mm Trunnion mount, electronic suspension, e-bike integrated
KOMPONENTEN	
LENKER	Giant Contact SLR Trail, carbon, 760mm (XS-S), 800mm (M-L)
GRIFFE	Liv Tactal Pro-E Single Lock-On Grips
VORBAU	Giant Contact SLR Trail, integrated, 40/45/50mm Reach, 7/9degree Sweep Adjust System
SATTELSTÜTZE	Rad+ travel adjust dropper, dropper, 30,9mm (XS&S:100~140mm/ M:140~170mm/ L:170~200mm)
SATTEL	Liv Sylvia E+
PEDALE	n/a
ANTRIEB	
SCHALTHEBEL	SRAM AXS Rocker Paddle, wireless electronic shifting
UMWERFER	MRP 1X HD2 custom co-molded chain guide
SCHALTWERK	SRAM GX Eagle AXS
BREMSSEN	SRAM Code R, hydraulic disc, 220mm[F] /200mm[R]
BREMSHEBEL	SRAM Code R
KASSETTE	SRAM XG-1275, 10-52T, 12-speed
KETTE	SRAM GX Eagle PowerLock
KURBEL	Praxis Performance Carbon e-crank arms(XS:160, S/M:165, L:170) SRAM X-SYNC Eagle 36T chain ring
TRETLAGER	n/a

LAUFRÄDER	
FELGEN	TRX 2 Hookless Clincher, 29" [F] / 27.5" [R], 30mm inner width
NABE	TRX 2 MTB Alloy Hub, 6 Bolt, Pawl Driver (3 Pawl 30T) SRAM XD, 110 x 15 [F] / 148 x 12 [R] Thru-axle
REIFEN	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)

GEOMETRIEDATEN

RAHMEN	XS	S	M	L
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Sitzrohrlänge (mm)	380	400	425	450
Sitzrohrwinkel	77.2° 78.0°	77.2° 78.0°	76.0° 76.7°	76.0° 76.7°
Oberrohrlänge (mm)	557 555	572 570	597 595	622 620
Steuerrohr-Länge (mm)	95	95	100	115
Steuerrohr-Winkel	65.7° 66.5°	65.7° 66.5°	65.8° 66.5°	65.8° 66.5°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	113 108	113 108	113 108	113 108
Radstand (mm)	1174 1175	1188 1190	1200 1201	1228 1229
Kettenstreben-Länge (mm)	447 447	447 447	447 447	447 447
Tretlager-Höhe (mm)	30 20	30 20	30 20	30 20
Stack (mm)	606 601	606 601	611 605	625 619
Reach (mm)	419 427	434 442	444 452	466 473
Überstandshöhe (mm)	722 730	726 735	717 726	711 723
Lenkerbreite (mm)	760	760	800	800
Vorbaulänge (mm)	40	40	40	50
Kurbellänge (mm)	160	160	165	165
Radgrösse	R27.5" / F	R27.5" / F	R27.5" / F	R27.5" / F

Spezifikations-, Preis- und Farbänderungen vorbehalten.