INTRIGUE X ADVANCED E+ ELITE 1



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro2 85Nm, powered by Yamaha
CONTROLLER	RideControl Ergo 3, RideControl GO integrated in T/T
DISPLAY	ANT+ Wireless display compatible
BATTERY	EnergyPak Smart Compact 400, EnergyPak Plus range extender compatible
ΣΚΕΛΕΤΌΣ	
ΜΕΓΈΘΗ	XS, S, M, L
ΧΡΏΜΑΤΑ	Airglow
ΣΚΕΛΕΤΌΣ	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension systemMX (front 29", rear 27.5")
ΠΙΡΟΎΝΙ	Fox 36 Performance Elite Live Valve, 150mm travel, 44mm offset, Grip2 damper, Boost 110x15QR, electronic adaptive suspension, e-bike integrated, e-bike integrated
ΑΝΆΡΤΗΣΗ	Fox Float X Live Valve, 185x52.5mm Trunnion mount, electronic suspension, e-bike integrated
ΕΞΑΡΤΉΜΑΤΑ	
ΤΙΜΌΝΙ	Giant Contact SLR Trail, carbon, 760mm (XS-S), 800mm (M-L)
GRIPS	Liv Tactal Pro-E Single Lock-On Grips
ΛΑΙΜΌΣ ΤΙΜΟΝΙΟΎ	Giant Contact SLR Trail, integrated,40/45/50mm Reach, 7/9degree Sweep Adjust System
ΛΑΙΜΌΣ ΣΈΛΛΑΣ	Rad+ travel adjust dropper, dropper, 30,9mm (XS&S:100~140mm/ M:140~170mm/ L:170~200mm)
ΣΈΛΛΑ	Liv Sylvia E+
ΠΕΝΤΆΛ	n/a
ΜΕΤΆΔΟΣΗ	
ΛΕΒΙΈ ΤΑΧΥΤΉΤΩΝ	SRAM AXS Rocker Paddle, wireless electronic shifting
ΝΤΕΡΑΓΙΈΡ ΕΜΠΡΌΣΘΙΟ	MRP 1X HD2 custom co-molded chain guide
ΝΤΕΡΑΓΙΈΡ ΟΠΊΣΘΙΟ.	SRAM GX Eagle AXS
ΦΡΈΝΑ	SRAM Code R, hydraulic disc, 220mm[F] /200mm[R]
ΜΑΝΈΤΤΕΣ ΦΡΈΝΩΝ	SRAM Code R
CASETTE Ή ΕΛΕΎΘΕΡΟ	SRAM XG-1275, 10-52T, 12-speed
ΑΛΥΣΊΔΑ	SRAM GX Eagle PowerLock
ΔΙΣΚΟΒΡΑΧΊΩΝΑΣ	Praxis Performance Carbon e-crank arms(XS:160, S/M:165, L:170) SRAM X-SYNC Eagle 36T chain ring
BOTTOM BRACKET	n/a

WHEELS	
ΣΤΕΦΆΝΙΑ	TRX 2 Hookless Clincher, 29" [F] / 27.5" [R], 30mm inner width
ΚΈΝΤΡΑ	TRX 2 MTB Alloy Hub, 6 Bolt, Pawl Driver (3 Pawl 30T) SRAM XD, 110 x 15 [F] / 148 x 12 [R] Thru-axle
ΕΛΑΣΤΙΚΆ	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)

ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΌΣ	XS	S	M	L
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Seat Tube Length (mm)	380	400	425	450
Seat Tube Angle	77,2° | 78,0°	77,2° | 78,0°	76,0° | 76,7°	76,0° | 76,7°
Top Tube Length (mm)	557 | 555	572 | 570	597 | 595	622 | 620
Head Tube Length (mm)	95	95	100	115
Head Tube Angle	65,7° | 66,5°	65,7° | 66,5°	65,8° | 66,5°	65,8° | 66,5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	113 | 108	113 | 108	113 | 108	113 | 108
Wheelbase (mm)	1174 | 1175	1188 | 1190	1200 | 1201	1228 | 1229
Chain Stay Length (mm)	447 | 447	447 | 447	447 | 447	447 | 447
Bottom Bracket Drop (mm)	30 | 20	30 | 20	30 | 20	30 | 20
Stack (mm)	606 | 601	606 | 601	611 | 605	625 | 619
Reach (mm)	419 | 427	434 | 442	444 | 452	466 | 473
Stand Over Height (mm)	722 | 730	726 | 735	717 | 726	711 | 723
Handlebar Width (mm)	760	760	800	800
Stem Length (mm)	40	40	40	50
Crank Length (mm)	160	160	165	165
Wheel Size	R27.5" / F	R27.5" / F	R27.5" / F	R27.5" / F

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση