

INTRIGUE X ADVANCED E+ ELITE 1



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro2 85Nm, powered by Yamaha
CONTROLLER	RideControl Ergo 3, grip integrated
DISPLAY	RideControl GO, frame integrated LED display ANT+ Wireless display compatible
BATTERY	EnergyPak Smart 400Wh EnergyPak Plus, range extender compatible
FRAME	
SIZES	XS, S, M, L
COLOURS	Airglow
FRAME	Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, flip chip, UDH hanger 12x148mm thru-axle
FORK	Fox 36 Performance Elite Live Valve, 150mm travel, 44mm offset, Grip2 damper, Boost 110x15QR, electronic adaptive suspension, e-bike integrated, e-bike integrated
SHOCK	Fox Float X Live Valve, 185x52.5mm Trunnion mount, electronic suspension, e-bike integrated
COMPONENTS	
HANDLEBAR	Giant Contact SLR Trail, carbon
GRIPS	Liv Tactal Pro-E Single Lock-On Grips
STEM	Giant Contact SLR Trail, integrated, 40/45/50mm Reach, 7/9degree Sweep Adjust System
SEATPOST	Rad+ travel adjust dropper
SADDLE	Liv Sylvia E+
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM AXS Rocker Paddle, wireless electronic shifting
FRONT DERAILLEUR	MRP 1X HD2 custom co-molded chain guide
REAR DERAILLEUR	SRAM GX Eagle AXS
BRAKES	SRAM Code R, hydraulic disc, 220mm[F] / 200mm[R]
BRAKE LEVERS	SRAM Code R
CASSETTE	SRAM XG-1275, 10-52T, 12-speed
CHAIN	SRAM GX Eagle PowerLock
CRANKSET	Praxis Performance Carbon e-crank arms
BOTTOM BRACKET	N/A

WHEELS	
RIMS	TRX 2 Hookless Clincher, 29" [F] / 27.5" [R], 30mm inner width
HUBS	TRX 2 MTB Alloy Hub, 6 Bolt, Pawl Driver (3 Pawl 30T) SRAM XD, 110 x 15 [F] / 148 x 12 [R] Thru-axle
TIRES	Maxxis Minion DHF 29x2.50" Foldable, TLR, EXO [F] Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers)

Price: \$14,499.00

GEOMETRY

FRAME	XS	S	M	L
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	380	400	425	450
Seat Tube Angle	77.2° 78.0°	77.2° 78.0°	76.0° 76.7°	76.0° 76.7°
Top Tube Length (mm)	557 555	572 570	597 595	622 620
Head Tube Length (mm)	95	95	100	115
Head Tube Angle	65.7° 66.5°	65.7° 66.5°	65.8° 66.5°	65.8° 66.5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	113 108	113 108	113 108	113 108
Wheelbase (mm)	1174 1175	1188 1190	1200 1201	1228 1229
Chain Stay Length (mm)	447 447	447 447	447 447	447 447
Bottom Bracket Drop (mm)	30 20	30 20	30 20	30 20
Stack (mm)	606 601	606 601	611 605	625 619
Reach (mm)	419 427	434 442	444 452	466 473
Stand Over Height (mm)	722 730	726 735	717 726	711 723
Stem Length (mm)	40	40	40	50
Crank Length (mm)	160	160	165	165
Wheel Size	R27.5" / F	R27.5" / F	R27.5" / F	R27.5" / F

*Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.*