

INTRIGUE X ADVANCED E+ ELITE 1



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro2 85Nm, powered by Yamaha
SENSOR	RideControl Ergo 3, RideControl GO integrated in T/T
DISPLAY	ANT+ Wireless display compatible
BATTERY	EnergyPak Smart Compact 400, EnergyPak Plus range extender compatible
FRAME	
SIZES	XS, S, M, L
COLORS	Airglow
FRAME	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension systemMX (front 29", rear 27.5")
FORK	Fox 36 Performance Elite Live Valve, 150mm travel, 44mm offset, Grip2 damper, Boost 110x15QR, electronic adaptive suspension, e-bike integrated, e-bike integrated
SHOCK	Fox Float X Live Valve, 185x52.5mm Trunnion mount, electronic suspension, e-bike integrated
COMPONENTS	
HANDLEBAR	Giant Contact SLR Trail, carbon, 760mm (XS-S), 800mm (M-L)
GRIPS	Liv Tactal Pro-E Single Lock-On Grips
STEM	Giant Contact SLR Trail, integrated, 40/45/50mm Reach, 7/9degree Sweep Adjust System
SEATPOST	Rad+ travel adjust dropper, dropper, 30,9mm (XS&S:100~140mm/ M:140~170mm/ L:170~200mm)
SADDLE	Liv Sylvia E+
PEDALS	n/a
DRIVETRAIN	
SHIFTERS	SRAM AXS Rocker Paddle, wireless electronic shifting
FRONT DERAILLEUR	MRP 1X HD2 custom co-molded chain guide
REAR DERAILLEUR	SRAM GX Eagle AXS
BRAKES	SRAM Code R, hydraulic disc, 220mm[F] /200mm[R]
BRAKE LEVERS	SRAM Code R
CASSETTE	SRAM XG-1275, 10-52T, 12-speed
CHAIN	SRAM GX Eagle PowerLock
CRANKSET	Praxis Performance Carbon e-crank arms(XS:160, S/M:165, L:170) SRAM X-SYNC Eagle 36T chain ring
BOTTOM BRACKET	n/a

WHEELS	
RIMS	TRX 2 Hookless Clincher, 29" [F] / 27.5" [R], 30mm inner width
HUBS	TRX 2 MTB Alloy Hub, 6 Bolt, Pawl Driver (3 Pawl 30T) SRAM XD, 110 x 15 [F] / 148 x 12 [R] Thru-axle
TIRES	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)

Price: ₹ 9,999.00

GEOMETRY

FRAME	S	M
	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	400	425
Seat Tube Angle	77.2° 78.0°	76.0° 76.7°
Top Tube Length (mm)	572 570	597 595
Head Tube Length (mm)	95	100
Head Tube Angle	65.7° 66.5°	65.8° 66.5°
Fork Rake (mm)	44	44
Trail (mm)	113 108	113 108
Wheelbase (mm)	1188 1190	1200 1201
Chain Stay Length (mm)	447 447	447 447
Bottom Bracket Drop (mm)	30 20	30 20
Stack (mm)	606 601	611 605
Reach (mm)	434 442	444 452
Stand Over Height (mm)	726 735	717 726
Handlebar Width (mm)	760	800
Stem Length (mm)	40	40
Crank Length (mm)	160	165
Wheel Size	R27.5" / F	R27.5" / F

The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city / country.