INTRIGUE X ADVANCED E+ ELITE 1



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro2 85Nm, powered by Yamaha
SENSOR	RideControl Ergo 3, RideControl GO integrated in T/T
DISPLAY	ANT+ Wireless display compatible
BATTERY	EnergyPak Smart Compact 400, EnergyPak Plus range extender compatible
CADRU	
MARIMI	XS, S, M, L
CULORI	Airglow
CADRU	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension systemMX (front 29", rear 27.5")
FURCA	Fox 36 Performance Elite Live Valve, 150mm travel, 44mm offset, Grip2 damper, Boost 110x15QR, electronic adaptive suspension, e-bike integrated, e-bike integrated
SOC	Fox Float X Live Valve, 185x52.5mm Trunnion mount, electronic suspension, e-bike integrated
COMPONENTE	
GHIDON	Giant Contact SLR Trail, carbon, 760mm (XS-S), 800mm (M-L)
GRIPS	Liv Tactal Pro-E Single Lock-On Grips
PIPA	Giant Contact SLR Trail, integrated,40/45/50mm Reach, 7/9degree Sweep Adjust System
TIJA SA	Rad+ travel adjust dropper, dropper, 30,9mm (XS&S:100~140mm/ M:140~170mm/ L:170~200mm)
SA	Liv Sylvia E+
PEDALE	n/a
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	SRAM AXS Rocker Paddle, wireless electronic shifting
SCHIMBATOR FATA	MRP 1X HD2 custom co-molded chain guide
SCHIMBATOR SPATE	SRAM GX Eagle AXS
FRANE	SRAM Code R, hydraulic disc, 220mm[F] /200mm[R]
MANETE FRANA	SRAM Code R
PINIOANE	SRAM XG-1275, 10-52T, 12-speed
LANT	SRAM GX Eagle PowerLock
ANGRENAJ	Praxis Performance Carbon e-crank arms(XS:160, S/M:165, L:170) SRAM X-SYNC Eagle 36T chain ring
BOTTOM BRACKET	n/a

ROTI	
JANTE	TRX 2 Hookless Clincher, 29" [F] / 27.5" [R], 30mm inner width
BUTUCI	TRX 2 MTB Alloy Hub, 6 Bolt, Pawl Driver (3 Pawl 30T) SRAM XD, 110 x 15 [F] / 148 x 12 [R] Thru-axle
ANVELOPE	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)

GEOMETRIE

CADRU	XS	S	M	L
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Seat Tube Length (mm)	380	400	425	450
Seat Tube Angle	77,2° | 78,0°	77,2° | 78,0°	76,0° | 76,7°	76,0° | 76,7°
Top Tube Length (mm)	557 | 555	572 | 570	597 | 595	622 | 620
Head Tube Length (mm)	95	95	100	115
Head Tube Angle	65,7° | 66,5°	65,7° | 66,5°	65,8° | 66,5°	65,8° | 66,5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	113 | 108	113 | 108	113 | 108	113 | 108
Wheelbase (mm)	1174 | 1175	1188 | 1190	1200 | 1201	1228 | 1229
Chain Stay Length (mm)	447 | 447	447 | 447	447 | 447	447 | 447
Bottom Bracket Drop (mm)	30 | 20	30 | 20	30 | 20	30 | 20
Stack (mm)	606 | 601	606 | 601	611 | 605	625 | 619
Reach (mm)	419 | 427	434 | 442	444 | 452	466 | 473
Stand Over Height (mm)	722 | 730	726 | 735	717 | 726	711 | 723
Handlebar Width (mm)	760	760	800	800
Stem Length (mm)	40	40	40	50
Crank Length (mm)	160	160	165	165
Wheel Size	R27.5" / F	R27.5" / F	R27.5" / F	R27.5" / F

Toate specificatiile enumerate se pot schimba fara notificare prealabila.