

INTRIGUE X ADVANCED E+ ELITE 1



ŠPECIFIKÁCIE

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro2 85Nm, powered by Yamaha
OVLÁDAČ	RideControl Ergo 3, RideControl GO integrated in T/T
OVLÁDACIA JEDNOTKA	ANT+ Wireless display compatible
BATÉRIA	EnergyPak Smart Compact 400, EnergyPak Plus range extender compatible
RÁM	
VELKOSTI	XS, S, M, L
FARBY	Airglow
RÁM	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension systemMX (front 29", rear 27.5")
VIDLICA	Fox 36 Performance Elite Live Valve, 150mm travel, 44mm offset, Grip2 damper, Boost 110x15QR, electronic adaptive suspension, e-bike integrated, e-bike integrated
TLMIČ	Fox Float X Live Valve, 185x52.5mm Trunnion mount, electronic suspension, e-bike integrated
KOMPONENTY	
RIADIDLÁ	Giant Contact SLR Trail, carbon, 760mm (XS-S), 800mm (M-L)
GRIPY	Liv Tactal Pro-E Single Lock-On Grips
PREDSTAVEC	Giant Contact SLR Trail, integrated, 40/45/50mm Reach, 7/9degree Sweep Adjust System
SEDLOVKA	Rad+ travel adjust dropper, dropper, 30,9mm (XS&S:100~140mm/ M:140~170mm/ L:170~200mm)
SEDADLO	Liv Sylvia E+
PEDÁLE	n/a
POHON	
RADENIE	SRAM AXS Rocker Paddle, wireless electronic shifting
PREŠMYKAČ	MRP 1X HD2 custom co-molded chain guide
PREHADZOVAČKA	SRAM GX Eagle AXS
BRZDY	SRAM Code R, hydraulic disc, 220mm[F] /200mm[R]
BRZDOVÉ PÁKY	SRAM Code R
KAZETA	SRAM XG-1275, 10-52T, 12-speed
REŤAZ	SRAM GX Eagle PowerLock
KLUKY	Praxis Performance Carbon e-crank arms(XS:160, S/M:165, L:170) SRAM X-SYNC Eagle 36T chain ring
STREDOVÉ ZLOŽENIE	n/a

KOLESÁ	
RÁFIKY	TRX 2 Hookless Clincher, 29" [F] / 27.5" [R], 30mm inner width
NÁBOJE	TRX 2 MTB Alloy Hub, 6 Bolt, Pawl Driver (3 Pawl 30T) SRAM XD, 110 x 15 [F] / 148 x 12 [R] Thru-axle
PNEUMATIKY	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
DOPLNKY	Tubeless kit (liquid, valves, levers, manual, tool)

Cena: 8 499 € (pôvodná cena 9 999 €)

GEOMETRIA

RÁM	XS		S		M		L		
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	
Dĺžka sedlovej trubky (mm)	380		400		425		450		
Uhol sedlovej trubky	77,2°		78,0°	77,2°	78,0°	76,0°	76,7°	76,0°	76,7°
Dĺžka hornej rámovej trubky (mm)	557	555	572	570	597	595	622	620	
Dĺžka hlavovej trubky (mm)	95		95		100		115		
Uhol hlavovej trubky	65,7°		66,5°	65,7°	66,5°	65,8°	66,5°	65,8°	66,5°
Offset vidlice (mm)	44		44		44		44		
Trail (mm)	113	108	113	108	113	108	113	108	
Rázvor (mm)	1174		1175	1188	1190	1200	1201	1228	1229
Dĺžka zadnej stavby (mm)	447	447	447	447	447	447	447	447	
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	30	20	30	20	30	20	30	20	
Stack - výška riadenia (mm)	606	601	606	601	611	605	625	619	
Reach (mm)	419	427	434	442	444	452	466	473	
Výška rámu od zeme (mm)	722	730	726	735	717	726	711	723	
Šírka riaditok (mm)	760		760		800		800		
Dĺžka predstavca (mm)	40		40		40		50		
Dĺžka kľúk (mm)	160		160		165		165		
Rozmer kolies	R27.5" / F		R27.5" / F		R27.5" / F		R27.5" / F		

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.