INTRIGUE X ADVANCED E+ ELITE 1



СПЕЦИФІКАЦІЯ

ТЕХНОЛОГІЯ HYBRID CYCLING	
ДВИГУН	SyncDrive Pro2 85Nm, powered by Yamaha
КОНТРОЛЕР	RideControl Ergo 3, RideControl GO integrated in T/T
ДИСПЛЕЙ	ANT+ Wireless display compatible
БАТАРЕЯ	EnergyPak Smart Compact 400, EnergyPak Plus range extender compatible
РАМА	
РОЗМІР	XS, S, M, L
КОЛІР	Airglow
КОНСТРУКЦІЯ	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension systemMX (front 29", rear 27.5")
ВИЛКА	Fox 36 Performance Elite Live Valve, 150mm travel, 44mm offset, Grip2 damper, Boost 110x15QR, electronic adaptive suspension, e-bike integrated, e-bike integrated
АМОРТИЗАТОР ЗАДНІЙ	Fox Float X Live Valve, 185x52.5mm Trunnion mount, electronic suspension, e-bike integrated
КОМПОНЕНТИ	
КЕРМО	Giant Contact SLR Trail, carbon, 760mm (XS-S), 800mm (M-L)
РУКОЯТКИ / ОБМОТКА	Liv Tactal Pro-E Single Lock-On Grips
ВИНОС КЕРМА	Giant Contact SLR Trail, integrated,40/45/50mm Reach, 7/9degree Sweep Adjust System
ВИНОС СІДЛА	Rad+ travel adjust dropper, dropper, 30,9mm (XS&S:100~140mm/ M:140~170mm/ L:170~200mm)
СІДЛО	Liv Sylvia E+
ПЕДАЛІ	n/a
ПРИВІД	
МАНЕТКИ	SRAM AXS Rocker Paddle, wireless electronic shifting
ПЕРЕМИКАЧ ПЕРЕДНІЙ	MRP 1X HD2 custom co-molded chain guide
ПЕРЕМИКАЧ ЗАДНІЙ	SRAM GX Eagle AXS
ГАЛЬМА	SRAM Code R, hydraulic disc, 220mm[F] /200mm[R]
ВАЖЕЛІ ГАЛЬМ	SRAM Code R
КАСЕТА	SRAM XG-1275, 10-52T, 12-speed
ЛАНЦЮГ	SRAM GX Eagle PowerLock
СИСТЕМА ШАТУНІВ	Praxis Performance Carbon e-crank arms(XS:160, S/M:165, L:170) SRAM X-SYNC Eagle 36T chain ring
КАРЕТКА	n/a

КОЛЕСА	
ОБОДИ	TRX 2 Hookless Clincher, 29" [F] / 27.5" [R], 30mm inner width
ВТУЛКИ	TRX 2 MTB Alloy Hub, 6 Bolt, Pawl Driver (3 Pawl 30T) SRAM XD, 110 x 15 [F] / 148 x 12 [R] Thru-axle
ШИНИ	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
ДОДАТКОВО	Tubeless kit (liquid, valves, levers, manual, tool)

ГЕОМЕТРІЯ

РАМА	XS	S	M	L
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Довжина підсідельної труби (mm)	380	400	425	450
Нахил підсідельної труби	77,2° | 78,0°	77,2° | 78,0°	76,0° | 76,7°	76,0° | 76,7°
Довжина верхньої труби (mm)	557 | 555	572 | 570	597 | 595	622 | 620
Висота кермової труби (mm)	95	95	100	115
Нахил кермової труби	65,7° | 66,5°	65,7° | 66,5°	65,8° | 66,5°	65,8° | 66,5°
Виліт вилки (mm)	44	44	44	44
Шлях вилки (mm)	113 | 108	113 | 108	113 | 108	113 | 108
Колісна база (mm)	1174 | 1175	1188 | 1190	1200 | 1201	1228 | 1229
Довжина нижнього пір'я рами (mm)	447 | 447	447 | 447	447 | 447	447 | 447
Провисання каретки (mm)	30 | 20	30 | 20	30 | 20	30 | 20
Ефективна висота (mm)	606 | 601	606 | 601	611 | 605	625 | 619
Ефективна довжина (mm)	419 | 427	434 | 442	444 | 452	466 | 473
Безпечна висота (mm)	722 | 730	726 | 735	717 | 726	711 | 723
Ширина керма (mm)	760	760	800	800
Довжина виносу (mm)	40	40	40	50
Довжина шатунів (mm)	160	160	165	165
Розмір коліс	R27.5" / F	R27.5" / F	R27.5" / F	R27.5" / F

Giant залишає за собою право змінювати специфікації без попереднього повідомлення.