

# INTRIGUE X ADVANCED E+ ELITE 2



## SPECS

HYBRID CYCLING TECHNOLOGY	
<b>MOTOR</b>	SyncDrive Pro2 85Nm, powered by Yamaha
<b>CONTROLLER</b>	RideControl Ergo 3, grip integrated
<b>DISPLAY</b>	RideControl GO, frame integrated LED display ANT+ Wireless display compatible
<b>BATTERY</b>	EnergyPak Smart 400Wh EnergyPak Plus, range extender compatible
FRAME	
<b>SIZES</b>	XS, S, M, L
<b>COLOURS</b>	Soap Suds/Aged Denim
<b>FRAME</b>	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension systemMX (front 29", rear 27.5")
<b>FORK</b>	Fox 36 Float Performance, 150mm travel, 44mm offset, Grip Damper, Boost 110x15QR, e-bike optimised
<b>SHOCK</b>	Fox Float Performance, EVOL Large Volume sleeve, 2pos, 185x52.5mm Trunnion mount, custom tuned
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact 35 Trail
<b>GRIPS</b>	Liv Tactal Pro-E Single Lock-On Grips
<b>STEM</b>	Giant Contact SL 35
<b>SEATPOST</b>	Giant Contact Switch, dropper
<b>SADDLE</b>	Liv Sylvia E+
<b>PEDALS</b>	N/A
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano SLX
<b>FRONT DERAILLEUR</b>	MRP HD2 co-moulded chain guide
<b>REAR DERAILLEUR</b>	Shimano Deore SLX, 12-speed, Shadow+
<b>BRAKES</b>	Shimano SLX BR-M7120, 4-piston, hydraulic disc, 203mm
<b>BRAKE LEVERS</b>	Shimano Deore SLX, I-spec EV
<b>CASSETTE</b>	Shimano CS-M6100-12, 10-51T, 12-speed
<b>CHAIN</b>	KMC e.12 Turbo, EcoProteq, e-bike optimized
<b>CRANKSET</b>	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set
<b>BOTTOM BRACKET</b>	N/A

WHEELS	
<b>RIMS</b>	Giant AM, alloy 29"[F], 27.5" [R]
<b>HUBS</b>	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
<b>SPOKES</b>	Sapim E-Lite [R] Race [F], e-bike optimized
<b>TIRES</b>	Maxxis Minion DHF 29x2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
<b>EXTRAS</b>	Tubeless kit (liquid, valves, levers)

**Price: \$9,499.00**

## GEOMETRY

FRAME	XS	S	M	L
	LOW   HIGH	LOW   HIGH	LOW   HIGH	LOW   HIGH
Seat Tube Length (mm)	380	400	425	450
Seat Tube Angle	77.2°   78.0°	77.2°   78.0°	76.0°   76.7°	76.0°   76.7°
Top Tube Length (mm)	557   555	572   570	597   595	622   620
Head Tube Length (mm)	95	95	100	115
Head Tube Angle	65.7°   66.5°	65.7°   66.5°	65.8°   66.5°	65.8°   66.5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	113   108	113   108	113   108	113   108
Wheelbase (mm)	1174   1175	1188   1190	1200   1201	1228   1229
Chain Stay Length (mm)	447   447	447   447	447   447	447   447
Bottom Bracket Drop (mm)	30   20	30   20	30   20	30   20
Stack (mm)	606   601	606   601	611   605	625   619
Reach (mm)	419   427	434   442	444   452	466   473
Stand Over Height (mm)	722   730	726   735	717   726	711   723
Stem Length (mm)	40	40	40	50
Crank Length (mm)	160	160	165	165
Wheel Size	R27.5" / F	R27.5" / F	R27.5" / F	R27.5" / F

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.