



INTRIGUE X ADVANCED E+ ELITE 2



ESPECIFICACIONES

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro2 85Nm, powered by Yamaha
SENSOR	RideControl Ergo 3, RideControl GO integrated in T/T
DISPLAY	ANT+ Wireless display compatible
BATERÍA	EnergyPak Smart 400EnergyPak Plus range extender compatible
CUADRO	
TALLAS	XS, S, M, L
COLORES	Soap Suds/Aged Denim
CUADRO	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension systemMX (front 29", rear 27.5")
TIJERA	Fox 36 Float Performance, 150mm travel, 44mm offset, Grip Damper, Boost 110x15QR, e-optimized
AMORTIGUADOR	Fox Float Performance, EVOL Large Volume sleeve, 2pos, 185x52.5mm Trunnion mount, custom tuned
COMPONENTES	
MANUBRIO	Giant Contact 35 Trail, 35x 760mm (XS-S), 780mm (M-L)
GRIPS	Liv Tactal Pro-E Single Lock-On Grips
POTENCIA	Giant Contact SL 35
POSTE DE ASIENTO	Giant Contact Switch, dropper, 30,9mm (XS-S: 100/ M:125/ L:150)
ASIENTO	Liv Sylvia E+
PEDALES	n/a
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano SLX
DESVIADOR	MRP HD2 co-moulded chain guide
CAMBIO TRASERO	Shimano Deore SLX, 12-speed, Shadow+
FRENOS	Shimano SLX BR-M7120, 4-piston, hydraulic disc, 203mm
PALANCAS DE FRENOS	Shimano Deore SLX, I-spec EV
CASSETTE	Shimano CS-M6100-12, 10-51T, 12-speed
CADENA	KMC e.12 Turbo, EcoProteq, e-bike optimized
MULTIPLICACIÓN	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (XS:160, S/M: 165, L:170)
EJE DE CENTRO	n/a

RUEDAS	
RUEDAS	Giant AM 29" [F]/ 27.5" [R], Tubeless ready, 30mm inner width, e-bike optimized
MAZAS	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
RAYOS	Sapim E-Lite [R] Race [F], e-bike optimized
NEUMÁTICOS	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)

Precio: \$169,990.00

GEOMETRÍA

CUADRO	XS		S		M		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longitud de la Base del Poste de Asiento (mm)	380		400		425		450	
Ángulo de la Base del Poste de Asiento	77.2°	78.0°	77.2°	78.0°	76.0°	76.7°	76.0°	76.7°
Longitud del Tubo Superior (mm)	557	555	572	570	597	595	622	620
Longitud del Telescopio (mm)	95		95		100		115	
Ángulo del Telescopio	65.7°	66.5°	65.7°	66.5°	65.8°	66.5°	65.8°	66.5°
Rake (mm)	44		44		44		44	
Trail (mm)	113	108	113	108	113	108	113	108
Distancia entre Ejes (mm)	1174	1175	1188	1190	1200	1201	1228	1229
Longitud de Vaina Inferior (mm)	447	447	447	447	447	447	447	447
Caída del Eje de Centro (mm)	30	20	30	20	30	20	30	20
Stack (mm)	606	601	606	601	611	605	625	619
Reach (mm)	419	427	434	442	444	452	466	473
Altura del Tubo Superior al Suelo (mm)	722	730	726	735	717	726	711	723
Ancho del Manubrio (mm)	760		760		800		800	
Longitud de la Potencia (mm)	40		40		40		50	
Longitud de la Biela (mm)	160		160		165		165	
Tamaño de las Ruedas	R27.5" / F		R27.5" / F		R27.5" / F		R27.5" / F	

Todas las especificaciones están sujetas a cambios sin previo aviso.