

INTRIGUE X ADVANCED E+ ELITE 2



CARACTÉRISTIQUES TECHNIQUES

TECHNOLOGIE HYBRID	
MOTOR	SyncDrive Pro2 85Nm, powered by Yamaha
SENSOR	RideControl Ergo 3, RideControl GO integrated in T/T
DISPLAY	ANT+ Wireless display compatible
BATTERIE	EnergyPak Smart 400EnergyPak Plus range extender compatible
CADRE	
TAILLES	XS, S, M, L
COLORIS	Soap Suds/Aged Denim
CADRE	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension systemMX (front 29", rear 27.5")
FOURCHE	Fox 36 Float Performance, 150mm travel, 44mm offset, Grip Damper, Boost 110x15QR, e-optimized
AMORTISSEUR	Fox Float Performance, EVOL Large Volume sleeve, 2pos, 185x52.5mm Trunnion mount, custom tuned
COMPOSANTS	
CINTRE	Giant Contact 35 Trail, 35x 760mm (XS-S), 780mm (M-L)
POIGNÉES	Liv Tactal Pro-E Single Lock-On Grips
POTENCE	Giant Contact SL 35
TIGE DE SELLE	Giant Contact Switch, dropper, 30,9mm (XS-S: 100/ M:125/ L:150)
SELLE	Liv Sylvia E+
PÉDALES	n/a
DÉRAILLEUR	
MANETTES DÉRAILLEUR	Shimano SLX
DÉRAILLEUR AVANT	MRP HD2 co-moulded chain guide
DÉRAILLEUR ARRIÈRE	Shimano Deore SLX, 12-speed, Shadow+
FREINS	Shimano SLX BR-M7120, 4-piston, hydraulic disc, 203mm
LEVIERS DE FREIN	Shimano Deore SLX, I-spec EV
CASSETTE	Shimano CS-M6100-12, 10-51T, 12-speed
CHAÎNE	KMC e.12 Turbo, EcoProteq, e-bike optimized
PÉDALIER	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (XS:160, S/M: 165, L:170)
PÉDALIER	n/a

ROUES	
JANTES	Giant AM 29" [F]/ 27.5" [R], Tubeless ready, 30mm inner width, e-bike optimized
MOYEUX	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
RAYONS	Sapim E-Lite [R] Race [F], e-bike optimized
PNEUS	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)

GÉOMÉTRIE

CADRE	XS		S		M		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longueur de tube de selle (mm)	380		400		425		450	
Angle de tube de selle	77,2°	78,0°	77,2°	78,0°	76,0°	76,7°	76,0°	76,7°
Longueur du tube supérieur (mm)	557	555	572	570	597	595	622	620
Longueur du tube de direction (mm)	95		95		100		115	
Angle du tube de direction	65,7°	66,5°	65,7°	66,5°	65,8°	66,5°	65,8°	66,5°
Déport de fourche (mm)	44		44		44		44	
Chasse (mm)	113	108	113	108	113	108	113	108
Empattement (mm)	1174	1175	1188	1190	1200	1201	1228	1229
Longueur des bases (mm)	447	447	447	447	447	447	447	447
Hauteur du boîtier de pédalier (mm)	30	20	30	20	30	20	30	20
Stack (mm)	606	601	606	601	611	605	625	619
Reach (mm)	419	427	434	442	444	452	466	473
Hauteur d'enjambement (mm)	722	730	726	735	717	726	711	723
Largeur de cintre (mm)	760		760		800		800	
Longueur de potence (mm)	40		40		40		50	
Longueur des manivelles (mm)	160		160		165		165	
Diamètre des roues	R27.5" / F		R27.5" / F		R27.5" / F		R27.5" / F	

Giant Suisse se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.