

INTRIGUE X ADVANCED E+ ELITE 2



SPECIFIKACIJE

HIBRIDNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Pro2 Mg, 85Nm, Magnasium Casing, powered by Yamaha, PedalPlus 6-Sensor technology
SENSOR	Giant RideControl Ergo3, grip integrated remote
PRIKAZ	Giant RideControl GO, frame integrated LED consoleOptional wireless ANT+ display
BATERIJA	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
OKVIR	
VELIČINE	XS, S, M, L
OKVIR	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system
VILICA	Fox 36 Float Performance E-Tuned, 29er, 150mm travel, 44mm offset, Grip Damper, Kabolt-X 110
AMORTIZER	Fox Float Performance, EVOL Large Volume sleeve, 2pos, 185x52.5mm Trunnion mount, custom tuned
KOMPONENTE	
VOLAN	Giant Contact 35 Trail, 35x 760mm (XS-S), 780mm (M-L)
GRIPS	Liv Tactal Pro-E Single Lock-On Grips
LULA VOLANA	Giant Contact SL 35
CIJEV SJEDALA	Tranz-X Rad+ dropper, 30,9mm, 30mm travel adjustable (XS/S:90-125mm, M:120-150mm, L:140-170mm)
SJEDALO	Liv Sylvia E+
PEDALE	N/A
POGON	
RUČICE MJENJAČA	Shimano SLX
PREDNJI MJENJAČ	MRP HD2 co-moulded chain guide
STRAŽNJI MJENJAČ	Shimano SLX, 12-speed, Shadow+
KOČNICE	Shimano SLX, BR-M7120, 4-piston, hydraulic disc, 203mm
RUČICE KOČNICA	Shimano SLX, I-spec EV
KAZETA	Shimano HG-M6100, 10-51T, 12-speed
LANAC	KMC e.12 Turbo, EcoProteq, e-bike optimized
POGON	Praxis N.W. 36T Cold Forged 4130 premium steel Praxis e-Cranks (Q-factor=168, XS/S:160, M/L:165)
OSOVINA POGONA (BB)	n/a

KOTAČI	
OBRUČI	E-TRA Hookless Tubeless ready Alloy 29 [F] / 27.5 [R] 30mm inner width
NABE	E-TRA MTB Alloy Hub, 6 Bolt, 110x15 [F] / 148x12 Shimano Micro-Spline Drive Body Pawl Driver (Pawl 36x2 T) Thru-axle [R]
GUME	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
DODACI	Tubeless kit (liquid, valves, levers, manual, tool)Inner tube supplied
DODACI	
SVJETLA	Optional:- Giant Recon series e-bike lights available and direct connectable

GEOMETRIJA

OKVIR	XS	S	M	L
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Dužina cijevi sjedala (mm)	380	400	425	445
Seat Post Insertion Depth (mm)	199	219	244	264
Kut cijevi sjedala	77,2°	77,2°	76,0°	76,0°
Dužina gornje cijevi (mm)	557 555	572 570	597 595	612 610
Dužina prednje cijevi (mm)	95	95	100	100
Kut vilice	65,7° 66,5°	65,7° 66,5°	65,8° 66,5°	65,8° 66,5°
Zakrivljenost vilice (offset) (mm)	44	44	44	44
Staza (mm)	113,1 108	113,1 108	113,1 108	113,1 108
Međuosovinski razmak kotača (mm)	1174 1175	1188 1190	1200 1201	1211 1212
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	447 447	447 447	447 447	447 447
Položaj osovine pogona (mm)	30 20	30 20	30 20	30 20
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	606 601	606 601	611 605	611 605
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	419 427	434 442	444 452	454 462
Prekoračna visina (mm)	722 730	726 735	717 726	717 726
Širina volana (mm)	760	760	800	800
Dužina lule volana (mm)	40	40	40	50
Dužina poluge pedale (mm)	160	160	165	165
Veličina kotača	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]

Sve navedene specifikacije podložne su promjeni bez prethodne najave.