

INTRIGUE X ADVANCED E+ ELITE 2



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro2 85Nm, powered by Yamaha
BEDIENINGSUNIT	RideControl Ergo 3, RideControl GO integrated in T/T
DISPLAY	ANT+ Wireless display compatible
ACCU	EnergyPak Smart 400EnergyPak Plus range extender compatible
FRAME	
MATEN	XS, S, M, L
KLEUREN	Soap Suds/Aged Denim
FRAME	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension systemMX (front 29", rear 27.5")
VOORVORK	Fox 36 Float Performance, 150mm travel, 44mm offset, Grip Damper, Boost 110x15QR, e-optimized
DEMPER	Fox Float Performance, EVOL Large Volume sleeve, 2pos, 185x52.5mm Trunnion mount, custom tuned
ONDERDELEN	
STUUR	Giant Contact 35 Trail, 35x 760mm (XS-S), 780mm (M-L)
HANDVATTEN	Liv Tactal Pro-E Single Lock-On Grips
STUURPEN	Giant Contact SL 35
ZADELPEN	Giant Contact Switch, dropper, 30,9mm (XS-S: 100/ M:125/ L:150)
ZADEL	Liv Sylvia E+
PEDALEN	n/a
AFMONTAGE	
SHIFTERS	Shimano SLX
VOORDERAILLEUR	MRP HD2 co-moulded chain guide
ACHTERDERAILLEUR	Shimano Deore SLX, 12-speed, Shadow+
REMMEN	Shimano SLX BR-M7120, 4-piston, hydraulic disc, 203mm
REMHENDELS	Shimano Deore SLX, I-spec EV
CASSETTE	Shimano CS-M6100-12, 10-51T, 12-speed
AANDRIJVING	KMC e.12 Turbo, EcoProteq, e-bike optimized
CRANKSET	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (XS:160, S/M: 165, L:170)
BOTTOM BRACKET	n/a

WIELSET	
VELGEN	Giant AM 29" [F]/ 27.5" [R], Tubeless ready, 30mm inner width, e-bike optimized
NAVEN	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
SPAKEN	Sapim E-Lite [R] Race [F], e-bike optimized
BANDEN	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRA'S	Tubeless kit (liquid, valves, levers, manual, tool)

Adviesprijs: € 6.999,00

GEOMETRIE

FRAME	XS		S		M		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Zitbuis Lengte (mm)	380		400		425		450	
Zitbuis Hoek	77,2°	78,0°	77,2°	78,0°	76,0°	76,7°	76,0°	76,7°
Frame Lengte (horizontaal) (mm)	557	555	572	570	597	595	622	620
Balhoofdbuis Lengte (mm)	95		95		100		115	
Balhoofdbuis Hoek	65,7°	66,5°	65,7°	66,5°	65,8°	66,5°	65,8°	66,5°
Vork Sprong (mm)	44		44		44		44	
Naloop (mm)	113	108	113	108	113	108	113	108
Wielbasis (mm)	1174	1175	1188	1190	1200	1201	1228	1229
Liggende achtervork lengte (mm)	447	447	447	447	447	447	447	447
Bottom Bracket Drop (mm)	30	20	30	20	30	20	30	20
Stack (mm)	606	601	606	601	611	605	625	619
Reach (mm)	419	427	434	442	444	452	466	473
Stand Over Height (mm)	722	730	726	735	717	726	711	723
Stuur breedte (mm)	760		760		800		800	
Stuurpen Lengte (mm)	40		40		40		50	
Cranklengte (mm)	160		160		165		165	
Wielmaat	R27.5" / F		R27.5" / F		R27.5" / F		R27.5" / F	

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.