

INTRIGUE X ADVANCED E+ ELITE 2



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro2 Mg, 85Nm, Magnasium Casing, powered by Yamaha, PedalPlus 6-Sensor technology
CONTROLLER	Giant RideControl Ergo3, grip integrated remote
DISPLAY	Giant RideControl GO, frame integrated LED consoleOptional wireless ANT+ display
BATTERY	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
FRAME	
SIZES	XS, S, M, L
FRAME	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system
FORK	Fox 36 Float Performance E-Tuned, 29er, 150mm travel, 44mm offset, Grip Damper, Kabolt-X 110
SHOCK	Fox Float Performance, EVOL Large Volume sleeve, 2pos, 185x52.5mm Trunnion mount, custom tuned
COMPONENTS	
HANDLEBAR	Giant Contact 35 Trail, 35x 760mm (XS-S), 780mm (M-L)
GRIPS	Liv Tactal Pro-E Single Lock-On Grips
STEM	Giant Contact SL 35
SEATPOST	Tranz-X Rad+ dropper, 30,9mm, 30mm travel adjustable (XS/S:90-125mm, M:120-150mm, L:140-170mm)
SADDLE	Liv Sylvia E+
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano SLX
FRONT DERAILLEUR	MRP HD2 co-moulded chain guide
REAR DERAILLEUR	Shimano SLX, 12-speed, Shadow+
BRAKES	Shimano SLX, BR-M7120, 4-piston, hydraulic disc, 203mm
BRAKE LEVERS	Shimano SLX, I-spec EV
CASSETTE	Shimano HG-M6100, 10-51T, 12-speed
CHAIN	KMC e.12 Turbo, EcoProteq, e-bike optimized
CRANKSET	Praxis N.W. 36T Cold Forged 4130 premium steel Praxis e-Cranks (Q-factor=168, XS/S:160, M/L:165)
BOTTOM BRACKET	n/a

WHEELS	
RIMS	E-TRA Hookless Tubeless ready Alloy 29 [F] / 27.5 [R] 30mm inner width
HUBS	E-TRA MTB Alloy Hub, 6 Bolt, 110x15 [F] / 148x12 Shimano Micro-Spline Drive Body Pawl Driver (Pawl 36x2 T) Thru-axle [R]
TIRES	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)Inner tube supplied
ACCESSORIES	
LIGHTING	Optional:- Giant Recon series e-bike lights available and direct connectable

GEOMETRY

FRAME	XS	S	M	L
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	380	400	425	450
Seat Post Insertion Depth (mm)	199	219	244	269
Seat Tube Angle	77,2°	77,2°	76,0°	76,0°
Top Tube Length (mm)	557 555	572 570	597 595	622 620
Head Tube Length (mm)	95	95	100	115
Head Tube Angle	65,7° 66,5°	65,7° 66,5°	65,8° 66,5°	65,8° 66,5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	113,1 108	113,1 108	113,1 108	113,1 108
Wheelbase (mm)	1174 1175	1188 1190	1200 1201	1228 1229
Chain Stay Length (mm)	447 447	447 447	447 447	447 447
Bottom Bracket Drop (mm)	30 20	30 20	30 20	30 20
Stack (mm)	606 601	606 601	611 605	625 619
Reach (mm)	419 427	434 442	444 452	466 473
Stand Over Height (mm)	722 730	726 735	717 726	711 723
Handlebar Width (mm)	760	760	800	800
Stem Length (mm)	40	40	40	50
Crank Length (mm)	160	160	165	165
Wheel Size	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]

All specifications listed are subject to change without notice.