



ŠPECIFIKÁCIE

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro2 85Nm, powered by Yamaha
OVLÁDAČ	RideControl Ergo 3, RideControl GO integrated in T/T
OVLÁDACIA JEDNOTKA	ANT+ Wireless display compatible
BATÉRIA	EnergyPak Smart 400EnergyPak Plus range extender compatible
RÁM	
VELKOSTI	XS, S, M, L
FARBY	Soap Suds/Aged Denim
RÁM	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension systemMX (front 29", rear 27.5")
VIDLICA	Fox 36 Float Performance, 150mm travel, 44mm offset, Grip Damper, Boost 110x15QR, e-optimized
TLMİČ	Fox Float Performance, EVOL Large Volume sleeve, 2pos, 185x52.5mm Trunnion mount, custom tuned
KOMPONENTY	
RIADIDLÁ	Giant Contact 35 Trail, 35x 760mm (XS-S), 780mm (M-L)
GRIPY	Liv Tactal Pro-E Single Lock-On Grips
PREDSTAVEC	Giant Contact SL 35
SEDOVKA	Giant Contact Switch, dropper, 30,9mm (XS-S: 100/ M:125/ L:150)
SEDADLO	Liv Sylvia E+
PEDÁLE	n/a
POHON	
RADENIE	Shimano SLX
PREŠMYKAČ	MRP HD2 co-moulded chain guide
PREHADZOVAČKA	Shimano Deore SLX, 12-speed, Shadow+
BRZDY	Shimano SLX BR-M7120, 4-piston, hydraulic disc, 203mm
BRZDOVÉ PÁKY	Shimano Deore SLX, I-spec EV
KAZETA	Shimano CS-M6100-12, 10-51T, 12-speed
REŤAZ	KMC e.12 Turbo, EcoProteq, e-bike optimized
KLUKY	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (XS:160, S/M: 165, L:170)
STREDOVÉ ZLOŽENIE	n/a

KOLESÁ	
RÁFIKY	Giant AM 29" [F]/ 27.5" [R], Tubeless ready, 30mm inner width, e-bike optimized
NÁBOJE	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
ŠPICE	Sapim E-Lite [R] Race [F], e-bike optimized
PNEUMATIKY	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
DOPLNKY	Tubeless kit (liquid, valves, levers, manual, tool)

Cena: nová cena 6 119 € (pôvodná cena 6 799 €)

GEOMETRIA

RÁM	XS		S		M		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dĺžka sedlovej trubky (mm)	380		400		425		450	
Uhol sedlovej trubky	77,2°	78,0°	77,2°	78,0°	76,0°	76,7°	76,0°	76,7°
Dĺžka hornej rámovej trubky (mm)	557	555	572	570	597	595	622	620
Dĺžka hlavovej trubky (mm)	95		95		100		115	
Uhol hlavovej trubky	65,7°	66,5°	65,7°	66,5°	65,8°	66,5°	65,8°	66,5°
Offset vidlice (mm)	44		44		44		44	
Trail (mm)	113	108	113	108	113	108	113	108
Rázvor (mm)	1174	1175	1188	1190	1200	1201	1228	1229
Dĺžka zadnej stavby (mm)	447	447	447	447	447	447	447	447
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	30	20	30	20	30	20	30	20
Stack - výška riadenia (mm)	606	601	606	601	611	605	625	619
Reach (mm)	419	427	434	442	444	452	466	473
Výška rámu od zeme (mm)	722	730	726	735	717	726	711	723
Šírka riadidok (mm)	760		760		800		800	
Dĺžka predstavca (mm)	40		40		40		50	
Dĺžka klúku (mm)	160		160		165		165	
Rozmer kolies	R27.5" / F		R27.5" / F		R27.5" / F		R27.5" / F	

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.