INTRIGUE X ADVANCED E+ ELITE 2



ŠPECIFIKÁCIE

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro2 Mg, 85Nm, Magnasium Casing, powered by Yamaha, PedalPlus 6-Sensor technology
OVLÁDAČ	Giant RideControl Ergo3, grip integrated remote
OVLÁDACIA JEDNOTKA	Giant RideControl GO, frame integrated LED consoleOptional wireless ANT+ display
BATÉRIA	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
RÁM	
VEĽKOSTI	XS, S, M, L
RÁM	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system
VIDLICA	Fox 36 Float Performance E-Tuned, 29er, 150mm travel, 44mm offset, Grip Damper, Kabolt-X 110
TLMIČ	Fox Float Performance, EVOL Large Volume sleeve, 2pos, 185x52.5mm Trunnion mount, custom tuned
KOMPONENTY	
RIADIDLÁ	Giant Contact 35 Trail, 35x 760mm (XS-S), 780mm (M-L)
GRIPY	Liv Tactal Pro-E Single Lock-On Grips
PREDSTAVEC	Giant Contact SL 35
SEDLOVKA	Tranz-X Rad+ dropper, 30,9mm, 30mm travel adjustable (XS/S:90-125mm, M:120-150mm, L:140-170mm)
SEDADLO	Liv Sylvia E+
PEDÁLE	N/A
POHON	
RADENIE	Shimano SLX
PREŠMYKAČ	MRP HD2 co-moulded chain guide
PREHADZOVAČKA	Shimano SLX, 12-speed, Shadow+
BRZDY	Shimano SLX, BR-M7120, 4-piston, hydraulic disc, 203mm
BRZDOVÉ PÁKY	Shimano SLX, I-spec EV
KAZETA	Shimano HG-M6100, 10-51T, 12-speed
REŤAZ	KMC e.12 Turbo, EcoProteq, e-bike optimized
KĽUKY	Praxis N.W. 36T Cold Forged 4130 premium steel Praxis e-Cranks (Q-factor=168, XS/S:160, M/L:165)
STREDOVÉ ZLOŽENIE	n/a

KOLESÁ	
RÁFIKY	E-TRA Hookless Tubeless ready Alloy 29 [F] / 27.5 [R] 30mm inner width
NÁBOJE	E-TRA MTB Alloy Hub, 6 Bolt, 110x15 [F] / 148x12 Shimano Micro-Spline Drive Body Pawl Driver (Pawl 36x2 T) Thru-axle [R]
PNEUMATIKY	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
DOPLNKY	Tubeless kit (liquid, valves, levers, manual, tool)Inner tube supplied
PRÍSLUŠENSTVO	
OSVETLENIE	Optional:- Giant Recon series e-bike lights available and direct connectable

Cena: 6 599 €

GEOMETRIA

RÁM	XS	S	M	L
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Dĺžka sedlovej trubky (mm)	380	400	425	450
Hĺbka vloženia sedlovky (mm)	199	219	244	269
Uhol sedlovej trubky	77,2°	77,2°	76,0°	76,0°
Dĺžka hornej rámovej trubky (mm)	557 | 555	572 | 570	597 | 595	622 | 620
Dĺžka hlavovej trubky (mm)	95	95	100	115
Uhol hlavovej trubky	65,7° | 66,5°	65,7° | 66,5°	65,8° | 66,5°	65,8° | 66,5°
Offset vidlice (mm)	44	44	44	44
Trail (mm)	113,1 | 108	113,1 | 108	113,1 | 108	113,1 | 108
Rázvor (mm)	1174 | 1175	1188 | 1190	1200 | 1201	1228 | 1229
Dĺžka zadnej stavby (mm)	447 | 447	447 | 447	447 | 447	447 | 447
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	30 | 20	30 | 20	30 | 20	30 | 20
Stack - výška riadenia (mm)	606 | 601	606 | 601	611 | 605	625 | 619
Reach (mm)	419 | 427	434 | 442	444 | 452	466 | 473
Výška rámu od zeme (mm)	722 | 730	726 | 735	717 | 726	711 | 723
Šírka riaditok (mm)	760	760	800	800
Dĺžka predstavca (mm)	40	40	40	50
Dĺžka kľúk (mm)	160	160	165	165
Rozmer kolies	[F] 29" [R	[F] 29" [R	[F] 29" [R	[F] 29" [R

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.