

INTRIGUE X ADVANCED E+ ELITE 3



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro2 85Nm, powered by Yamaha
CONTROLLER	RideControl Ergo 3, grip integrated
DISPLAY	RideControl GO, frame integrated LED display ANT+ Wireless display compatible
BATTERY	EnergyPak Smart 400Wh EnergyPak Plus, range extender compatible
FRAME	
SIZES	XS, S, M, L
COLOURS	Mirage/Cordovan
FRAME	Advanced-Grade Composite front triangle, ALUXX SL-Grade rear triangle, 140mm Maestro suspension, flip chip, UDH hanger 12x148mm thru-axle
FORK	RockShox 35 Gold RL DebonAir, 150mm travel, 44mm offset, MotionControl rebound and lockout control, 15x110 Boost, Maxle Stealth, e-bike optimised
SHOCK	Rock Shox Deluxe Select R, DebonAir, 185x52.5mm Trunion mount, custom tuned
COMPONENTS	
HANDLEBAR	Giant Contact 35 Trail
GRIPS	Liv Tactal Pro-E Single Lock-On Grips
STEM	Giant Contact SL 35
SEATPOST	Giant Contact Switch, dropper
SADDLE	Liv Sylvia E+
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano Deore
FRONT DERAILLEUR	MRP HD2 co-moulded chain guide
REAR DERAILLEUR	Shimano Deore, 12-speed
BRAKES	Shimano BR-M420, 4-piston, hydraulic disc, 203mm
BRAKE LEVERS	Shimano Deore, I-spec EV
CASSETTE	Shimano CS-M6100-12, 10-51T, 12-speed
CHAIN	KMC e.12 Turbo, EcoProteq, e-bike optimized
CRANKSET	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set
BOTTOM BRACKET	N/A

WHEELS	
RIMS	Giant AM, alloy 29"[F], 27.5" [R]
HUBS	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
SPOKES	Sapim E-Lite [R] Race [F], e-bike optimized
TIRES	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers)

Price: \$8,799.00

GEOMETRY

FRAME	XS	S	M	L
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	380	400	425	450
Seat Tube Angle	77.2° 78.0°	77.2° 78.0°	76.0° 76.7°	76.0° 76.7°
Top Tube Length (mm)	557 555	572 570	597 595	622 620
Head Tube Length (mm)	95	95	100	115
Head Tube Angle	65.7° 66.5°	65.7° 66.5°	65.8° 66.5°	65.8° 66.5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	113 108	113 108	113 108	113 108
Wheelbase (mm)	1174 1175	1188 1190	1200 1201	1228 1229
Chain Stay Length (mm)	447 447	447 447	447 447	447 447
Bottom Bracket Drop (mm)	30 20	30 20	30 20	30 20
Stack (mm)	606 601	606 601	611 605	625 619
Reach (mm)	419 427	434 442	444 452	466 473
Stand Over Height (mm)	722 730	726 735	717 726	711 723
Stem Length (mm)	40	40	40	50
Crank Length (mm)	160	160	165	165
Wheel Size	R27.5" / F	R27.5" / F	R27.5" / F	R27.5" / F

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.