

INTRIGUE X ADVANCED E+ ELITE 3



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro2 85Nm, powered by Yamaha, PedalPlus 6-Sensor technology
CONTROLLER	Giant RideControl Ergo3, grip integrated remote
DISPLAY	Giant RideControl GO, frame integrated LED consoleOptional wireless ANT+ display
BATTERY	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
FRAME	
SIZES	XS, S, M, L
FRAME	Advanced-grade composite frame, AluXX SL-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system
FORK	Marzocchi Bomber Z2 E-Tuned, 29er, 150mm travel, 44mm offset, RAIL damper Sweep-Adj, Kabolt 110
SHOCK	Fox Float Performance, EVOL Large Volume sleeve, 2pos, 185x52.5mm Trunnion mount, custom tuned
COMPONENTS	
HANDLEBAR	Giant Contact 35 Trail, 35x 760mm (XS-S), 780mm (M-L)
GRIPS	Liv Tactal Pro-E Single Lock-On Grips
STEM	Giant Contact SL 35
SEATPOST	Tranz-X Rad+ dropper, 30,9mm, 30mm travel adjustable (XS/S:90-125mm, M:120-150mm, L:140-170mm)
SADDLE	Liv Sylvia E+
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano Deore
FRONT DERAILLEUR	MRP HD2 co-moulded chain guide
REAR DERAILLEUR	Shimano Deore 12-speed, Shadow+
BRAKES	Shimano BR-MT420, 4-piston, hydraulic disc, 203mm
BRAKE LEVERS	Shimano Deore, I-spec EV
CASSETTE	Shimano CS-M6100-12, 10-51T, 12-speed
CHAIN	KMC e.12 Turbo, EcoProteq, e-bike optimized
CRANKSET	Praxis N.W. 36T Cold Forged 4130 premium steel Praxis e-Cranks (Q-factor=168, XS/S:160, M/L:165)
BOTTOM BRACKET	n/a

WHEELS	
RIMS	AM30, Tubeless ready, 30mm inner width, 29" [F] / 27.5" [R]
HUBS	Shimano MT410 Boost, Center-Lock, 110x15 [F] 148x12 Shimano Micro-Spline Drive Body Thru-axle [R]
SPOKES	Sapim E-Lite [R] Race [F], e-bike optimized
TIRES	Maxxis Minion DHF 29x2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)Inner tube supplied
ACCESSORIES	
LIGHTING	Optional:- Giant Recon series e-bike lights available and direct connectable

Suggested Retail Price (CDN): \$7,499.00

FRAME GEOMETRY

FRAME	XS		S		M		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	380	400	425	450				
Seat Post Insertion Depth (mm)	199	219	244	269				
Seat Tube Angle	77.2°	77.2°	76.0°	76.0°				
Top Tube Length (mm)	557 555	572 570	597 595	622 620				
Head Tube Length (mm)	95	95	100	115				
Head Tube Angle	65.7° 66.5°	65.7° 66.5°	65.8° 66.5°	65.8° 66.5°				
Fork Rake (mm)	44	44	44	44				
Trail (mm)	113.1 108	113.1 108	113.1 108	113.1 108				
Wheelbase (mm)	1174 1175	1188 1190	1200 1201	1228 1229				
Chain Stay Length (mm)	447 447	447 447	447 447	447 447				
Bottom Bracket Drop (mm)	30 20	30 20	30 20	30 20				
Stack (mm)	606 601	606 601	611 605	625 619				
Reach (mm)	419 427	434 442	444 452	466 473				
Stand Over Height (mm)	722 730	726 735	717 726	711 723				
Handlebar Width (mm)	760	760	800	800				
Stem Length (mm)	40	40	40	50				
Crank Length (mm)	160	160	165	165				
Wheel Size	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]				

All prices and specifications are subject to change without notice.